

AX100692-S Faceplates and Panels - 110 CROSS-CONNECT 300PR LEGS



For more Information
please call

1-800-Belden1



General Description:

110 CROSS-CONNECT, WIRING BLOCK 300-PAIR WITH LEGS

Usage (Overall)

| | |
|------------------------|---|
| Suitable Applications: | IBDN System 1200, TIA Category 5E, ISO Class E, 1000BASE-T |
| Related Parts: | 110 CROSS-CONNECT CONNECTING BLOCK 4-PAIR & 5-PAIR, 110 CROSS-CONNECT LABEL STRIP |

Physical Characteristics (Connectivity)

Capacity

| | |
|----------------|----------|
| Max. Capacity: | 300-PAIR |
|----------------|----------|

Access

| | |
|-------------------|-------|
| Front Connection: | Flush |
| Termination Area: | Front |

Dimensions

Dimensions:

| Height (in.) | Width (in.) | Depth (in.) |
|--------------|-------------|-------------|
| 10.780 | 10.690 | 3.330 |

Materials

Materials:

| Description | Material |
|-------------|-------------------|
| Block | Plastic - UL94V-0 |

Color

| | |
|--------|--------|
| Color: | Almond |
|--------|--------|

Weight

| | |
|---------|------------|
| Weight: | 1.650 lbs. |
|---------|------------|

Included Parts

| | |
|-----------------|--|
| Included Parts: | 1x300PR WIRING BLOCK WITH LEGS, 6xLABEL STRIPS |
|-----------------|--|

Packaging

| | |
|------------|---|
| Packaging: | Individually packaged in a clear plastic bag. |
|------------|---|

Mechanical Characteristics (Connectivity)

Termination Interface:

| Termination | Connection | Durabilities |
|-------------|----------------|----------------|
| Front | IDC Connection | 200 insertions |

| | |
|---------------------------------|--|
| Storage Temperature Range: | -40°C To +70°C |
| Installation Temperature Range: | -10°C To +60°C |
| Operating Temperature Range: | -10°C To +60°C |
| Tool Compatibility: | 110 Cross-Connect Connecting Tool AX100749 |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|-----------------------------|
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/30/2008 |
| Safety Listing: | Bi-national Standard Listed |

Suitability

| | |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

AX100692-S Faceplates and Panels - 110 CROSS-CONNECT 300PR LEGS

Transmission Characteristics (Connectivity)

Notes (Overall)

Notes: For additional information about this product, visit our web site at <http://www.belden.com>

Product Family

Part Numbers:

| Description | Item Number |
|---|-------------|
| WIRING BLOCK 100-PAIR W/O LEGS | AX100690-S |
| WIRING BLOCK 100-PAIR WITH LEGS | AX100691-S |
| WIRING BLOCK 300-PAIR W/O LEGS | AX100692-S |
| WIRING BLOCK 100-PAIR WITH LEGS WITH 4-PAIR CONNECTING BLOCKS | AX100693-S |
| WIRING BLOCK 100-PAIR WITH LEGS WITH 5-PAIR CONNECTING BLOCKS | AX100694-S |
| WIRING BLOCK 300-PAIR WITH LEGS WITH 4-PAIR CONNECTING BLOCKS | AX100695-S |
| WIRING BLOCK 300-PAIR WITH LEGS WITH 5-PAIR CONNECTING BLOCKS | AX100696-S |
| DISTRIBUTION RING, SMALL | AX100703-X |
| DISTRIBUTION RING, LARGE | AX100704-X |
| CABLE MANAGEMENT TROUGH W/O LEGS | AX100705-S |
| CABLE MANAGEMENT TROUGH WITH LEGS | AX100706-S |
| CONNECTING BLOCK 4-PAIR | AX100707-S |
| CONNECTING BLOCK 5-PAIR | AX100708-S |
| LABEL STRIP CLEAR | AX100721-S |

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|------------|-------|-------------|-------|-------|-----------------------------|
| AX100692-S | 1 EA | 1.650 LB | | | 300PR 110 WIRING BLOCK LEGS |

Revision Number: 0 Revision Date: 02-08-2011

© 2016 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.