



- Notes
- 1 The recommended clamp torque of ref. No. ① : 4 to 4.5 N·m .
LOCTITE 263, HENKEL JAPAN or equivalent is recommended to prevent
ref. No. ① from loosening.
 - 2 The recommended clamp torque of ref. No. ④ to be 0.65 to 0.7 N·m .
 3. The cable pull and twisting strength, waterproof tightness and other characteristics
may differ, depending on the cable structure. Please confirm before the use.

2	PPS	(Black) UL94V-0	4	Stainless steel	M3×0.5×8				
1	Brass	Black chrome plating	3	Acrylonitrile butadiene rubber	(Grey)				
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS			
UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
HIROSE ELECTRIC CO., LTD.		APPROVED	HY. KOBAYASHI		18. 02. 26		DRAWING NO.	EDC-110612-31-00	
		CHECKED	HY. KOBAYASHI		18. 02. 26		PART NO.	JR21WCC-14(31)	
		DESIGNED	TH. KAMEYA		18. 02. 23		CODE NO.	CL114-2061-7-31	
		DRAWN	MK. INOUE		18. 02. 14			1	