

Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
Rating	Operating Temperature Range	-25°C to +60°C	Storage Temperature Range	-25°C to +60°C	
	Voltage	—	Operating Humidity Range	—	
	Curent	—	Applicable Cable	—	
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
General Examination	Visually and by measuring instrument.	According to drawing.	X	X	
Marking	Confirmed visually.		X	X	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
	0				
REMARK			APPROVED	NM. NISHIMATSU	17. 02. 07
			CHECKED	NM. NISHIMATSU	17. 02. 07
			DESIGNED	MO. SHIMOYAMA	17. 02. 07
Unless otherwise specified, refer to IEC 60512.			DRAWN	JY. IGA	17. 02. 07
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-120682-06-00
HRS	SPECIFICATION SHEET		PART NO.	TM11APA1-88P (06)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL222-2783-4-06	△ 1/1