



900 MHz 8 dBi LH Circular Polarized Patch Antenna

Antennas Technical Data Sheet

PE51FP1007

Features

- Left Hand Circular Polarized
- 4 ft coax lead with N-Male Connector
- Compact size, low profile
- Lightweight ABS Radome

Applications

- 800 MHz, 900 MHz ISM Bands
- Wireless LAN systems
- Wireless Video Links
- RFID, GSM, SCADA
- LPWAN, LoRA, IoT, M2M applications

Description

The Hyperlink model PE51FP1007 series are high performance left hand circular polarized wall mount panel antennas designed to operate in the 900 MHz (860-960 MHz) band. These antennas feature circular polarization which makes them ideal for RFID applications. Compact and low profile, the PE51FP1007 antennas feature 8dBi of gain with a 65° beam width. Right-Hand versions are also available, the PE51FP1008 series.

Configuration

Design	Panel
Band Type	Single
Radiation Pattern	Directional
Polarization	LHCP
Cable Type	Coax lead
Cable Length	48 in [121.92 cm]
Connector Type	N Male
Number of Ports	1

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Input VSWR		1.5:1		
Impedance		50		Ohms
Gain		8		dBi
Input Power			25	Watts

Specifications by Band

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	902-928					MHz
Gain	8					dBi
Horizontal Beam Width	65					Degees
Vertical Beam Width	65					Degees
Maximum Input Power	25					Watts

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [900 MHz 8 dBi LH Circular Polarized Patch Antenna PE51FP1007](#)



900 MHz 8 dBi LH Circular Polarized Patch Antenna

Antennas Technical Data Sheet

PE51FP1007

Mechanical Specifications

Radome Material

ASA

Size

Overall Length

8.5 in [215.9 mm]

Width

8.5 in [215.9 mm]

Height

1.1 in [27.94 mm]

Weight

1.17 lbs [530.7 g]

Environmental Specifications

Temperature

Operating Range

-20 to +60 deg C

Environment


UL-94HB

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Antenna RF Patterns



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [900 MHz 8 dBi LH Circular Polarized Patch Antenna PE51FP1007](#)



900 MHz 8 dBi LH Circular Polarized Patch Antenna

Antennas Technical Data Sheet

PE51FP1007

900 MHz 8 dBi LH Circular Polarized Patch Antenna from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [900 MHz 8 dBi LH Circular Polarized Patch Antenna PE51FP1007](https://www.pasternack.com/single-antenna-8-dbi-gain-n-pe51fp1007-p.aspx)

URL: <https://www.pasternack.com/single-antenna-8-dbi-gain-n-pe51fp1007-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE51FP1007 CAD Drawing
900 MHz 8 dBi LH Circular Polarized Patch Antenna

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	2/12/2020	M.MILLER



UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

.X = ± .2	[5.08]	FRACTIONS
.XX = ± .02	[.51]	± 1/32
.XXX = ± .005	[.13]	ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305]	± .1 [25]	/ -0
12 [305] < L ≤ 60 [1524]	± .2 [51]	/ -0
60 [1524] < L ≤ 120 [3048]	± .4 [102]	/ -0
120 [3048] < L ≤ 300 [7620]	± .6 [152]	/ -0
300 [7620] < L	± .5% L	/ -0

ALL DIMENSIONS SHOWN
ARE FOR REFERENCE ONLY.

THIRD-ANGLE PROJECTION

THE INFORMATION AND
DESIGN IN THIS DOCUMENT
IS THE PROPERTY OF
PASTERNAK CORPORATION
ALL RIGHTS RESERVED.

SHEET 1 OF 1

SCALE N/A

PASTERNAK
an INFINITI® brand

Pasternack Enterprises, Inc.
P.O. Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com

SIZE A CAGE CODE 53919 DRAWN BY K.DANG ITEM NO. PE51FP1007 REV A

REGULATORY COMPLIANCE:
EU RoHS Directive (Most Recent Released Version)
THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE
WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.