

## 24.5 to 29.5 MHz, Omni Marine Antenna, 3 dBi, UHF Female (SO239) Connector, White, Stainless Steel Radome, Vertical Polarization

### PEMAROM1006



#### Features

- Marine grade omni antenna
- Stainless steel whip
- L bracket
- SO239 Female connector
- 24.5 to 29.5 MHz, 3 dBi
- Yacht, boats and other marine vehicles
- Single pole long antenna
- IP67 rated antenna

#### Applications

- Marine Radios
- Vessel communications
- Navigation Systems: RDF and LORAN-C.
- Weather monitoring
- Marine Beacons
- DSC emergency distress signals.

#### Description

The Pasternack PEMAROM1006 is a single band omni marine antenna that ships on the same day as ordered. Our vertical polarized antenna with 24.5 to 29.5 MHz frequency range has a UHF female connector. This antenna with a white radome made of stainless steel has an overall length of 56.50 inch, a width of 1.2 inch, and a weight of 0.66 lbs.

Pasternack's PEMAROM1006 is a single band antenna operating from 24.5 to 29.5 MHz with 3 dBi gain. The omni directional antenna has a maximum input VSWR of 1.5:1.

Pasternack has one of the largest in-stock collections of omni directional antennas with our wide selection of superior quality RF parts, that ship same day. Make your online purchase right now to take advantage of our same-day shipping. For further information on similar products, our expert technical support and knowledgeable sales team can help you get the ideal single band omni antenna as per your requirement.

#### Configuration

|                   |                  |
|-------------------|------------------|
| Design            | Marine           |
| Band Type         | Single           |
| Radiation Pattern | Omni Directional |
| Polarization      | Vertical         |
| Cable Type        | SO239            |
| Connector Type    | UHF Female       |
| Number of Ports   | 1                |

#### Electrical Specifications

| Description               | Minimum | Typical | Maximum | Units   |
|---------------------------|---------|---------|---------|---------|
| Frequency Range           | 24.5    |         | 29.5    | MHz     |
| Input VSWR                |         |         | 1.5:1   |         |
| Impedance                 |         | 50      |         | Ohms    |
| Gain                      |         | 3       |         | dBi     |
| Horizontal (Azimuth) HPBW |         | 360     |         | Degrees |
| Input Power               |         |         | 50      | Watts   |

#### Mechanical Specifications

|                 |                 |
|-----------------|-----------------|
| Radome Material | stainless steel |
|-----------------|-----------------|

24.5 to 29.5 MHz, Omni Marine Antenna,  
3 dBi, UHF Female (SO239) Connector, White,  
Stainless Steel Radome, Vertical Polarization

## PEMAROM1006



### Size

|        |                     |
|--------|---------------------|
| Length | 56.5 in [143.51 cm] |
| Width  | 1.2 in [30.48 mm]   |
| Height | 1.2 in [30.48 mm]   |
| Weight | 0.88 lbs [399.16 g] |

### Environmental Specifications

#### Temperature

|                 |                  |
|-----------------|------------------|
| Operating Range | -40 to +80 deg C |
|-----------------|------------------|

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:

### Typical Radiation Pattern

### Appendix

**Electrical Downtilt:** Angle in the antenna's elevation pattern in which the maximum gain occurs.

**Gain:** Antenna's average gain.

**Front to Back Ratio @ 180°±30°:** Average difference between the antenna's maximum gain and the maximum gain in the antenna's back lobe over ±30° angles.

**Cross-polarization Ratio (dB):** Typical difference between the co-polarization and cross-polarization gain across the sector's 3 dB Beam Width.

Dedicated to serving the needs of the Wireless Internet Service Provider (WISP) market, KP Performance Antennas offers purpose built products that reliably perform in the field. KP Performance Antennas product line consists of Yagi, Grid, Omni, Dish and other style antennas that operate in the 900 MHz, 2.4 GHz, 3 GHz, and 5 GHz frequencies.

24.5 to 29.5 MHz, Omni Marine Antenna, 3 dBi, UHF Female (SO239) Connector, White, Stainless Steel Radome, Vertical Polarization from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [24.5 to 29.5 MHz, Omni Marine Antenna, 3 dBi, UHF Female \(SO239\) Connector, White, Stainless Steel Radome, Vertical Polarization PEAROM1006](#)

URL: <https://www.pasternack.com/3-dbi-antenna-24.5-29.5-mhz-uhf-female-connector-pearom1006-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Pasternack Enterprises reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack Enterprises does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack Enterprises does not assume liability arising out of the use of any part or document.

PEMAROM1006 CAD Drawing

24.5 to 29.5 MHz, Omni Marine Antenna, 3 dBi, UHF Female (SO239)

Connector, White, Stainless Steel Radome, Vertical Polarization

