

# THERMOMARK E.SLEEVE - Applicator



1192932

<https://www.phoenixcontact.com/us/products/1192932>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Applicator for the efficient printing and application of E-WMS... shrink sleeves and marking sleeves on wires and cables in a single automated process step

## Product description

To achieve maximum efficiency in wire and cable identification processes, combine a standard roll printer from the THERMOMARK E SERIES with the THERMOMARK E.SLEEVE applicator. This provides you with an automated printing and application system that enables you to achieve time savings of up to 75% compared to manual identification processes. The THERMOMARK E.SLEEVE cuts the ready-printed E-WMS... shrink sleeves and marking sleeves in continuous format to the appropriate length, opens the individual markers, and feeds them in as far as the removal position so that the user can apply the finished markers to the wire/cable very easily. This unique system enables the efficient and demand-oriented creation of custom marker lengths between 15 mm/0.59" and 51 mm/2.0". Automated identification of all types of cylindrical objects that have a diameter of between 0.8 mm/0.03" and 8.5 mm/0.33" is supported.

Scope of supply:

THERMOMARK E.SLEEVE, TM E.WIRE/E.SLEEVE-PR pressure roller (1259203), multilingual packing slip

## Your advantages

- Time savings of up to 75% compared to manual printing and application processes
- Consistently high level of efficiency over the entire working day through intuitive handling, which helps reduce costs
- Planning accuracy with regard to productivity and quality: in the case of order peaks, productivity can be increased significantly using the same number of employees
- Reduction in the number of user errors through intuitive step-by-step guidance along the entire identification process as well as automatic data processing from CAE systems and other popular file formats for data exchange
- Cost efficiency by using shrink sleeves in continuous format
- No setup effort, thanks to automatic diameter adjustment
- Automatic object detection
- Shrink sleeve markers cut to variable lengths from 15 mm ... 51 mm
- For cylindrical objects with a diameter ranging from 0.8 mm ... approx. 8.5 mm
- Quick and easy mounting of the applicator on the roll printer via hexagon screw
- The applicator is connected via the D-SUB interface on the roll printer and is detected automatically by the software

## Commercial data

|                        |         |
|------------------------|---------|
| Item number            | 1192932 |
| Packing unit           | 1 pc    |
| Minimum order quantity | 1 pc    |
| Sales key              | BG01    |
| Product key            | BG122Z  |

# THERMOMARK E.SLEEVE - Applicator



1192932

<https://www.phoenixcontact.com/us/products/1192932>

|                                      |               |
|--------------------------------------|---------------|
| GTIN                                 | 4063151244699 |
| Weight per piece (including packing) | 3,600 g       |
| Weight per piece (excluding packing) | 2,440 g       |
| Customs tariff number                | 84433210      |
| Country of origin                    | DE            |

# THERMOMARK E.SLEEVE - Applicator



1192932

<https://www.phoenixcontact.com/us/products/1192932>

## Technical data

### Product properties

|              |                             |
|--------------|-----------------------------|
| Product type | Printing system accessories |
|--------------|-----------------------------|

### Electrical properties

#### Supply

|                      |         |
|----------------------|---------|
| Supply voltage range | 24 V DC |
|----------------------|---------|

### Dimensions

|        |        |
|--------|--------|
| Width  | 244 mm |
| Height | 148 mm |
| Length | 200 mm |

### Environmental and real-life conditions

#### Ambient conditions

|                                 |                |
|---------------------------------|----------------|
| Ambient temperature (operation) | 5 °C ... 35 °C |
|---------------------------------|----------------|

# THERMOMARK E.SLEEVE - Applicator



1192932

<https://www.phoenixcontact.com/us/products/1192932>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 19140192 |
| ECLASS-12.0 | 19140192 |
| ECLASS-13.0 | 19140192 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001675 |
|----------|----------|

# THERMOMARK E.SLEEVE - Applicator

1192932

<https://www.phoenixcontact.com/us/products/1192932>



## Accessories

### THERMOMARK E.300 D US - Thermal transfer printer

1287033

<https://www.phoenixcontact.com/us/products/1287033>



Thermal transfer printer with internal rewinder for printing all materials in roll format with a print resolution of 300 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.

---

### THERMOMARK E.300 US - Thermal transfer printer

1287021

<https://www.phoenixcontact.com/us/products/1287021>



Thermal transfer printer for printing all materials in roll format with a print resolution of 300 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.

# THERMOMARK E.SLEEVE - Applicator

1192932

<https://www.phoenixcontact.com/us/products/1192932>



## THERMOMARK E.600 D US - Thermal transfer printer

1287040

<https://www.phoenixcontact.com/us/products/1287040>



Thermal transfer printer with internal rewinder for printing all materials in roll format with a print resolution of 600 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.

---

## THERMOMARK E.600 US - Thermal transfer printer

1287029

<https://www.phoenixcontact.com/us/products/1287029>



Thermal transfer printer for printing all materials in roll format with a print resolution of 600 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.

# THERMOMARK E.SLEEVE - Applicator

1192932

<https://www.phoenixcontact.com/us/products/1192932>



## THERMOMARK E.300 DOUBLE - Thermal transfer printer

1472379

<https://www.phoenixcontact.com/us/products/1472379>



Thermal transfer printer for one-sided and double-sided printing of materials in roll format with a print resolution of 300 dpi. Suitable for long-term use in production and for large print volumes, as large rolls can also be processed.

---

## TM-RIBBON 40 BK 105 - Ink ribbon

1259008

<https://www.phoenixcontact.com/us/products/1259008>



Ink ribbon, for the E-WMS... product group in combination with the THERMOMARK E.SLEEVE applicator and the WMS... and WMS-2 HF... product groups in combination with conventional roll printers, length: 300 m, roll length: 300 m, width: 40 mm, color: black

# THERMOMARK E.SLEEVE - Applicator

1192932

<https://www.phoenixcontact.com/us/products/1192932>



## TM E.WIRE/E.SLEEVE-PR - Pressure roller

1259203

<https://www.phoenixcontact.com/us/products/1259203>



Pressure roller for all E-WM... and E-WMS... materials (for material width of up to 30 mm/1.18")

---

## THERMOMARK E SERIES CASE - Case

1450747

<https://www.phoenixcontact.com/us/products/1450747>



Transport case for the E.SLEEVE, E.VARIO, E.WIRE, and E.WRAP applicators of the THERMOMARK E SERIES and their accessories.



# THERMOMARK E.SLEEVE - Applicator



1192932

<https://www.phoenixcontact.com/us/products/1192932>

## TM E.SLEEVE-CARDBOARD BOX - Original packaging

1371341

<https://www.phoenixcontact.com/us/products/1371341>



Original packaging incl. inlay for safe transportation of the THERMOMARK E. SLEEVE

---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)