

FL MGUARD 4102 PCIE - Router



1357842

<https://www.phoenixcontact.com/us/products/1357842>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Security appliance, PCIe card, 10/100/1000 Mbps, NAT, advanced firewall, VPN

Your advantages

- Central management tool
- Maximum security
- Maximum performance
- Integration of IT and OT security
- mGuard security technology

Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 1357842 |
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | DN30 |
| Product key | DNN312 |
| GTIN | 4063151686802 |
| Weight per piece (including packing) | 172.9 g |
| Weight per piece (excluding packing) | 90.68 g |
| Customs tariff number | 85176200 |
| Country of origin | DE |

Technical data

Interfaces

Ethernet

| | |
|----------------------|--|
| Connection method | RJ45 |
| Transmission speed | 10/100/1000 Mbps |
| Transmission physics | Ethernet in RJ45 twisted pair |
| Transmission length | 100 m (per segment) |
| Signal LEDs | WAN link, WAN activity, LAN link, LAN activity |
| No. of channels | 2 (RJ45 ports) |

System properties

System requirements

| | |
|--------------------|------------------------|
| Supported browsers | HTTPS support required |
|--------------------|------------------------|

Product properties

| | |
|--------------|--|
| Product type | Security routers without DIN rail mounting |
| Format | PCIe |

Insulation characteristics

| | |
|------------------|---------------------------------------|
| Protection class | III (IEC 61140, EN 61140, VDE 0140-1) |
|------------------|---------------------------------------|

Electrical properties

| | |
|-------------------|--|
| Local diagnostics | One LED per port Activity LED red |
| | One LED per port Link active Green LED |

Supply

| | |
|-------------------------|--------------|
| Power supply connection | via PCIe bus |
|-------------------------|--------------|

Environmental and real-life conditions

Ambient conditions

| | |
|---|-------------------------------|
| Degree of protection | IP00 |
| Ambient temperature (operation) | -20 °C ... 70 °C |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Permissible humidity (operation) | 5 % ... 95 % (non-condensing) |

Mounting

| | |
|---------------|--------------|
| Mounting type | PCIe x1-Slot |
|---------------|--------------|

EMC data

| | |
|---------------------------------|--|
| Conformance with EMC directives | IEC 61000-6-2 IEC 61000-4-2 (ESD) 6 kV contact discharge, 8 kV air discharge |
| | IEC 61000-6-2 IEC 61000-4-3 (immunity to radiated interference) 10 V/m (80 MHz ... 6000 MHz) |

FL MGUARD 4102 PCIE - Router



1357842

<https://www.phoenixcontact.com/us/products/1357842>

| | |
|-------------------------------|---|
| | IEC 61000-6-2 IEC 61000-4-4 (burst) |
| | IEC 61000-6-2 IEC 61000-4-5 (surge) power line: 1 kV (line/earth), 0.5 kV (line/line), 1 kV data line |
| | IEC 61000-6-2 IEC 61000-4-6 (immunity to conducted interference) 10 V (150 kHz ... 80 MHz) |
| Noise immunity | EN 61000-6-2:2005 |
| Electromagnetic compatibility | Conformance with EMC Directive 2014/30/EU |
| Noise emission | EN 61000-6-4 |

Signaling

| | |
|----------------|------------------------|
| Status display | Link/activity per port |
|----------------|------------------------|

FL MGUARD 4102 PCIE - Router



1357842

<https://www.phoenixcontact.com/us/products/1357842>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1357842>



cUL Recognized
Approval ID: E238705



UL Recognized
Approval ID: E238705

cULus Recognized

FL MGUARD 4102 PCIE - Router



1357842

<https://www.phoenixcontact.com/us/products/1357842>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 19170406 |
| ECLASS-12.0 | 19170406 |
| ECLASS-13.0 | 19170406 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC001478 |
|----------|----------|

1357842

<https://www.phoenixcontact.com/us/products/1357842>

Environmental product compliance

EU RoHS

| | |
|---|--------|
| Fulfills EU RoHS substance requirements | Yes |
| Exemption | 7(c)-I |

China RoHS

| | |
|--|---|
| Environment friendly use period (EFUP) | EFUP-50 |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

EU REACH SVHC

| | |
|-------------------------------------|---|
| REACH candidate substance (CAS No.) | 4,4'-isopropylidenediphenol(CAS: 80-05-7) |
|-------------------------------------|---|

FL MGUARD 4102 PCIE - Router



1357842

<https://www.phoenixcontact.com/us/products/1357842>

Accessories

MGUARD SECURE VPN CLIENT LIC - License

2702579

<https://www.phoenixcontact.com/us/products/2702579>



License for mGuard Secure VPN Client v11.x

FL MGUARD DM UNLIMITED - Software

2981974

<https://www.phoenixcontact.com/us/products/2981974>



Central device management software for MGUARD devices for any number of devices in the field. For installation on a PC. No additional licenses required. Download trial version for up to 10 devices.

FL MGUARD 4102 PCIE - Router



1357842

<https://www.phoenixcontact.com/us/products/1357842>

SD FLASH 2GB - Program / configuration memory

2988162

<https://www.phoenixcontact.com/us/products/2988162>



Program and configuration memory, for extending the internal flash memory, pluggable, 2 GB.

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com