Product data sheet

Specification





IEC contactor, Easy TeSys DPE, nonreversing, 12A, 3P, 5HP at 480V AC, 120V 50/60Hz coil

DPE12G7

Main

Range	Easy TeSys	
Product name	Easy TeSys DPE	
product or component type	Contactor	
Device short name	DPE	
contactor application Resistive load Motor control		
Utilisation category	AC-4 AC-1 AC-3	
poles description	3P	
Pole contact composition	3 NO	
Auxiliary contact composition	1 NO	
[le] rated operational current	12 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit 25 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit	
[Uc] control circuit voltage	120 V AC 50/60 Hz	
Motor power kW	3 kW 220230 V AC 50/60 Hz 5.5 kW 380400 V AC 50/60 Hz 5.5 kW 415 V AC 50/60 Hz 5.5 kW 440 V AC 50/60 Hz 7.5 kW 500 V AC 50/60 Hz 7.5 kW 660690 V AC 50/60 Hz	
Motor power hp	0.33 hp at 115 V AC 50/60 Hz for 1 phase motors 1 hp at 230/240 V AC 50/60 Hz for 1 phase motors 2 hp at 200/208 V AC 50/60 Hz for 3 phases motors 2 hp at 230/240 V AC 50/60 Hz for 3 phases motors 5 hp at 460/480 V AC 50/60 Hz for 3 phases motors 7.5 hp at 575/600 V AC 50/60 Hz for 3 phases motors	

Complementary

Maximum Operational Voltage	Power circuit <= 690 V AC 25400 Hz Power circuit <= 300 V DC
[Ith] conventional free air thermal current	10 A (at 140 °F (60 °C)) for signalling circuit 25 A (at 140 °F (60 °C)) for power circuit
Irms rated making capacity	250 A at 440 V for power circuit conforming to IEC 60947 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1
Rated breaking capacity	250 A at 440 V for power circuit conforming to IEC 60947
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 25 A gG at <= 690 V coordination type 1 for power circuit 20 A gG at <= 690 V coordination type 2 for power circuit
Average impedance	2.5 mOhm - Ith 25 A 50 Hz for power circuit

Power dissipation per pole	1.56 W AC-1
	0.2 W AC-3
Electrical durability	0.6 Mcycles 25 A AC-1 <= 440 V 1 Mcycles 12 A AC-3 <= 440 V
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Control circuit type	AC 50/60 Hz
Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out: 0.30.6 Uc at 50/60 Hz (at <158 °F (70 °C)) Operational: 0.81.1 Uc at 50 Hz (at <140 °F (60 °C)) Operational: 0.851.1 Uc at 60 Hz (at <140 °F (60 °C)) Operational: 11.1 Uc at 50/60 Hz (at <158 °F (70 °C))
Inrush power in VA	70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C))
Hold-in power consumption in VA	7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat dissipation	23 W 50/60 Hz
Operating time	1222 ms closing 419 ms opening
Mechanical durability	10 Mcycles
Maximum operating rate	3600 cyc/h 140 °F (60 °C)
Auxiliary contacts type	Mechanically linked 1 NO IEC 60947-5-1
Minimum switching current	5 mA for signalling circuit
Minimum switching voltage	17 V for signalling circuit
Insulation resistance	> 10 MOhm for signalling circuit
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Signalling circuit frequency	25400 Hz
Connections - terminals	Power circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end
	Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end
Tightening torque	stiffness: flexible without cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable
Tightening torque mounting support	stiffness: flexible without cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Philips No 2 Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm

Width	1.8 in (45 mm)
Depth	3.4 in (86 mm)
net weight	0.71 lb(US) (0.32 kg)

Environment

[Ui] rated insulation voltage	Power circuit 690 V IEC 60947-4-1 Power circuit 600 V CSA Power circuit 600 V UL Signalling circuit 690 V IEC 60947-1
Overvoltage category	III
Pollution degree	3
[Uimp] rated impulse withstand voltage	6 kV IEC 60947
Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 60947-4-1
Product certifications	UL CSA
IP degree of protection	IP22 front face IEC 60529
Ambient air temperature for storage	-76176 °F (-6080 °C)
Ambient air temperature for operation	-40140 °F (-4060 °C)
Operating altitude	02000 m
Fire resistance	1562 °F (850 °C) IEC 60695-2-1
Mechanical robustness	Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms)

Packing Units

r doming office		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.7 in (9.5 cm)	
Package 1 Width	1.8 in (4.5 cm)	
Package 1 Length	3.03 in (7.7 cm)	
Package 1 Weight	12.3 oz (350.0 g)	
Unit Type of Package 2	S02	
Number of Units in Package 2	16	
Package 2 Height	5.9 in (15.0 cm)	
Package 2 Width	11.8 in (30.0 cm)	
Package 2 Length	15.7 in (40.0 cm)	
Package 2 Weight	13.040 lb(US) (5.915 kg)	
Unit Type of Package 3	P06	
Number of Units in Package 3	256	
Package 3 Height	303.15 in (770.0 cm)	
Package 3 Width	23.6 in (60.0 cm)	

Package 3 Length	31.5 in (80.0 cm)
Package 3 Weight	227.38 lb(US) (103.14 kg)



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information