Product data sheet

Specification





IEC contactor, Easy TeSys DPE, nonreversing, 38A, 3P, 20HP at 480V AC, 240V 50/60Hz coil

DPE38U7

Main

Range	Easy TeSys	
Product name	Easy TeSys DPE	
product or component type	Contactor	
Device short name	DPE	
contactor application	Resistive load Motor control	
Utilisation category	AC-4 AC-1 AC-3	
poles description	3P	
Pole contact composition	3 NO	
Auxiliary contact composition	1 NO	
[le] rated operational current 38 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit 52 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit		
[Uc] control circuit voltage	240 V AC 50/60 Hz	
Motor power kW	9 kW 220230 V AC 50/60 Hz 18.5 kW 380400 V AC 50/60 Hz 18.5 kW 415 V AC 50/60 Hz 18.5 kW 440 V AC 50/60 Hz 18.5 kW 500 V AC 50/60 Hz 18.5 kW 660690 V AC 50/60 Hz	
Motor power hp	2 hp at 115 V AC 50/60 Hz for 1 phase motors 5 hp at 230/240 V AC 50/60 Hz for 1 phase motors 10 hp at 200/208 V AC 50/60 Hz for 3 phases motors 10 hp at 230/240 V AC 50/60 Hz for 3 phases motors 20 hp at 460/480 V AC 50/60 Hz for 3 phases motors 25 hp at 575/600 V AC 50/60 Hz for 3 phases motors	

Complementary

Maximum Operational Voltage	Power circuit <= 690 V AC 25400 Hz Power circuit <= 300 V DC
[lth] conventional free air thermal current	10 A (at 140 °F (60 °C)) for signalling circuit 50 A (at 140 °F (60 °C)) for power circuit
Irms rated making capacity	140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 550 A at 440 V for power circuit conforming to IEC 60947
Rated breaking capacity	550 A at 440 V for power circuit conforming to IEC 60947
Associated fuse rating	10 A gG for signalling circuit conforming to IEC 60947-5-1 63 A gG at <= 690 V coordination type 1 for power circuit 63 A gG at <= 690 V coordination type 2 for power circuit
Average impedance	2 mOhm - Ith 50 A 50 Hz for power circuit

Jun 28, 2024 Life Is On Schneider

Power dissipation per pole	2 W AC-3
	5 W AC-1
Electrical durability	1 Mcycles 38 A AC-3 <= 440 V 0.6 Mcycles 52 A AC-1 <= 440 V
Safety reliability level	B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1
Control circuit type	AC 50/60 Hz
Coil technology	Without built-in suppressor module
Control circuit voltage limits	Drop-out: 0.30.6 Uc at 50/60 Hz (at <158 °F (70 °C)) Operational: 0.81.1 Uc at 50 Hz (at <140 °F (60 °C)) Operational: 0.851.1 Uc at 60 Hz (at <140 °F (60 °C)) Operational: 11.1 Uc at 50/60 Hz (at <158 °F (70 °C))
Inrush power in VA	70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C))
Hold-in power consumption in VA	7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))
Heat dissipation	23 W 50/60 Hz
Mechanical durability	10 Mcycles
Maximum operating rate	3600 cyc/h 140 °F (60 °C)
Auxiliary contacts type	Mechanically linked 1 NO IEC 60947-5-1
Minimum switching current	5 mA for signalling circuit
Minimum switching voltage	17 V for signalling circuit
Insulation resistance	> 10 MOhm for signalling circuit
Non-overlap time	1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact
Signalling circuit frequency	25400 Hz
Connections - terminals	Power circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end Power circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 2 0.0020.004 in² (12.5 mm²) - cable stiffness: flexible with cable end Power circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Power circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: flexible without cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 0.0020.004 in² (14 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: flexible with cable end Control circuit: screw clamp terminals 1 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end Control circuit: screw clamp terminals 2 0.0020.006 in² (14 mm²) - cable stiffness: solid without cable end
Tightening torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Philips No 2 Power circuit 22.1 lbf.in (2.5 N.m) screw clamp terminals flat Ø 6 mm Power circuit 22.1 lbf.in (2.5 N.m) screw clamp terminals Philips No 2
mounting support	Rail Plate
Height	3.3 in (85 mm)
Width	1.8 in (45 mm)

Depth	3.6 in (92 mm)
net weight	0.827 lb(US) (0.375 kg)

Environment

[Ui] rated insulation voltage	Power circuit 690 V IEC 60947-4-1 Power circuit 600 V CSA Power circuit 600 V UL Signalling circuit 690 V IEC 60947-1
Overvoltage category	III
Pollution degree	3
[Uimp] rated impulse withstand voltage	6 kV IEC 60947
Standards	CSA C22.2 No 14 EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 60947-4-1
Product certifications	UL CSA
IP degree of protection	IP20 front face IEC 60529
Ambient air temperature for storage	-76176 °F (-6080 °C)
Ambient air temperature for operation	-40140 °F (-4060 °C)
Operating altitude	02000 m
Fire resistance	1562 °F (850 °C) IEC 60695-2-1
Mechanical robustness	Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor open 10 Gn for 11 ms) Shocks contactor closed 15 Gn for 11 ms)

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.6 in (9.2 cm)
Package 1 Width	1.8 in (4.5 cm)
Package 1 Length	3.3 in (8.5 cm)
Package 1 Weight	14.6 oz (415.0 g)



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

⊘	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information