




Connectors > Contacts > Connector Contacts



Contact Type: **Socket**

Contact Mating Area Plating Material: **Tin**

Wire Contact Termination Area Plating Material: **Pre-Tin**

Operating Voltage: **600 VAC**

Contact Retention Within Housing: **With**

Features

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features

Mating Square Post Dimension	1.14 mm[.045 in]
Contact Underplating Material Thickness	.762 μm[30 μin]
Wire Contact Termination Area Plating Thickness	2.54 μm[100 μin]
Wire Contact Termination Area Plating Material Finish	Bright
Contact Mating Area Plating Material Thickness	2.54 μm[100 μin]
Contact Orientation	Straight
Contact Underplating Material	Nickel
Contact Type	Socket
Contact Mating Area Plating Material	Tin
Wire Contact Termination Area Plating Material	Pre-Tin
Contact Retention Within Housing	With
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	13 A



Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	Without
-------------------------	---------

Dimensions

Compatible Insulation Diameter Range	1.5 – 3.1 mm [.06 – .122 in]
Wire Size	1.31 mm²

Usage Conditions

Operating Temperature Range	-40 – 105 °C [-40 – 221 °F]
-----------------------------	-----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Packaging Features

Packaging Method	Bag
------------------	-----

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability






Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous






materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 1586055-1 VAL-U-LOK SKT BR SN 16AWG	 TE Part # 2238017-1 VAL-U-LOK SKT BR SN 18-22AWG	 TE Part # 2825206-1 VAL-U-LOK PIN HCS SN 16AWG	 TE Part # 2825207-1 VAL-U-LOK SKT HCS SN 16AWG
 TE Part # 2825208-1 VAL-U-LOK PIN 16AWG HCS SN LP	 TE Part # 2825210-1 VAL-U-LOK PIN HCS SN 18-22AWG	 TE Part # 2825211-1 VAL-U-LOK SKT HCS SN 18-22AWG	 TE Part # 2825212-1 VAL-U-LOK PIN HCS TN 22-18 LP
 TE Part # 2825213-1 VAL-U-LOK SKT HCS SN 22-18 LP	 TE Part # 1586055-3 VAL-U-LOK SKT PHBZ SN 16AWG		

Customers Also Bought


 TE Part #205843-2 CPC RECPT ASSEMBLY SIZE 23-63	 TE Part #1-1734839-0 FPC CONN. 0.5MM PITCH T/C,10P	 TE Part #1-794954-6 16P RCPT VAL-U-LOK V2	 TE Part #1-794954-2 12P RCPT VAL-U-LOK V2
---	--	---	---





TE Part #1-1469373-1

ATCA GUIDE MODULE RA FEMALE



TE Part #2029112-3

3P RCPT SR VAL-U-LOK GW



TE Part #2-1879208-5

CPF 0402 100R 0.1% 25PPM 1K RL



TE Part #2825208-1

VAL-U-LOK PIN 16AWG HCS SN LP



TE Part #L9000231-01

Antenna WIFI6 2.4/5/6 GHz RPC MHF4 100

Documents

Product Drawings

VAL-U-LOK SKT 16AWG HCS SN LP

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2825209-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2825209-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2825209-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English