

SBCP-87HY2R2H

Aliases (UPIO87HY2R2H00)

KEMET, SBCP-87HY, Through-Hole Drum, 2200 nH, 30%, 5mm

	←		D		►
		1	0	1	
		1	0	1	
, F-	► 	<u>}_</u>			
•		<	S		

Click here for the 3D model.

Dimensions	
D	9.5mm MAX
L	8.5mm MAX
S	5mm +/-0.5mm
LL	3.5mm +1/-0.5mm
F	0.6mm NOM

Packaging Specifications

Typical Component Weight	1.6 g
Packaging	Ammo
Packaging Quantity	2000

General Information				
Series	SBCP-87HY			
Style	Ferrite			
Description	Radial Leaded, Ferrite Power Inductors			
Features	DC-DC Converters, Nickel-Zinc (NiZn) Ferrite Core			
RoHS	Yes			
Lead	Wire Leads			
Core	Ferrite			
Notes	Contains 4 Reels of 500 pieces each.			

Specifications	
Inductance	2200 nH
Inductance Tolerance	30%
Temperature Range	-20/+105°C
Shielded	No
Current	4 Amps
DC Resistance	0.03 Ohms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.