

# Compact USB-C Wall Charger - GaN Technology, 65W PD Charging, White

MODEL NUMBER: U280-W01-65C1-G



Travel-sized USB-C charger provides up to 65W to quickly and efficiently charge your MacBook Pro or Windows laptop at home or on the move.

## Features

### 65W USB Type-C Charger Gets Your Mobile Device Ready in a Hurry, Wherever You Are

This single-port USB charger lets you quickly and safely charge your USB-C mobile device. Plug it into any NEMA 1-15R, NEMA 5-15R or NEMA 5-15/20R AC outlet to ensure your laptop, smartphone, tablet or other USB-C device charges at its fastest possible speed. The USB-C port supports USB Power Delivery (PD) 3.0 charging up to 5V 3A (15W), 9V 3A (27W), 12V 3A (36W), 15V 3A (45W) and 20V 3.25A (65W). A blue LED lets you know when the charger is ready.

### Gallium Nitride Technology Allows High-Wattage Capacity in a Compact Package

This USB wall charger is smaller and lighter than most standard wall chargers that come with a laptop. Ideal for travel, it is designed using GaN technology, which has a higher power density than silicon and provides higher efficiency than standard USB-C fast chargers. It also operates under much cooler temperatures, despite its small size, meaning it won't get hot while charging your device.

### Built-In Auto-Sensing Adjusts to Proper Power Level to Get Your Device to 100%

The USB-C port features auto-sensing technology that automatically adjusts to your device's appropriate power level. The unit protects against overheating, overcurrent and overcharging. In fact, it stops charging as soon as your device's battery is at full capacity.

### Folding Plug Design Perfectly Sized for Travel

The compact USB Type-C charger, small enough to fit in your hand, is easy to carry in your purse, suitcase, laptop bag or backpack. The NEMA 1-15P plug folds into the unit when not in use to shield it from damage and prevent it from snagging or scratching your bag's contents.

## Specifications

| OVERVIEW             |                |
|----------------------|----------------|
| UPC Code             | 037332262646   |
| Charging Form Factor | Direct Plug-In |

## Highlights

- Ideal for charging smartphones, tablets, e-readers and laptops while traveling
- USB-C PD 3.0 port supports a maximum power capacity of 65W for fast charging
- Gallium nitride (GaN) technology generates less heat to support high-efficiency charging
- Connects to any NEMA 1-15R, 5-15R or 5-15/20R AC outlet for immediate charging
- Charger with folding plug is perfectly sized for traveling in your backpack or purse

## Applications

Charge a smartphone, tablet, laptop or other mobile device without taking up a valuable USB port on your computer

## Package Includes

U280-W01-65C1-G USB-C Wall Charger, GaN, USB-C PD 3.0, 65W



Powering Business Worldwide

**TRIPP-LITE**  
by **EAT•N**

|                                                |                                                                              |
|------------------------------------------------|------------------------------------------------------------------------------|
| Product Type                                   | Wall Charger                                                                 |
| Device Compatibility                           | Amazon Kindle; Chromebook; Laptop; Phone; Tablet                             |
| Technology                                     | USB 3.x                                                                      |
| <b>INPUT</b>                                   |                                                                              |
| Nominal Input Voltage(s) Supported             | 100V AC; 240V AC                                                             |
| Voltage Compatibility (VAC)                    | 100; 110; 120; 125; 127; 200; 208; 220; 230; 240                             |
| Input Frequency                                | 50 / 60 Hz                                                                   |
| Input Plug Type                                | NEMA 1-15P (NON-POLARIZED)                                                   |
| Input Current                                  | 1.7A (Max)                                                                   |
| <b>OUTPUT</b>                                  |                                                                              |
| Overload Protection                            | Yes                                                                          |
| <b>POWER</b>                                   |                                                                              |
| Power Consumption (Watts)                      | 65                                                                           |
| USB Power Delivery (PD) Charging Support       | Yes                                                                          |
| USB Power Delivery (PD) Charging Specification | 3.0                                                                          |
| <b>CONNECTIONS</b>                             |                                                                              |
| Number of Ports                                | 1                                                                            |
| Side A - Connector 1                           | NEMA 1-15P (NON-POLARIZED)                                                   |
| Side B - Connector 1                           | USB C (FEMALE)                                                               |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b>   |                                                                              |
| LED Indicators                                 | Blue - Power                                                                 |
| <b>CHARGING</b>                                |                                                                              |
| Number of Charging Ports                       | 1                                                                            |
| Total Charging Amps                            | 3.25A                                                                        |
| Total Charging Watts                           | 65                                                                           |
| Charging Method                                | USB                                                                          |
| Charging Method Detail                         | Power Delivery 3.0                                                           |
| Charging Port Type                             | USB C (FEMALE)                                                               |
| Charging Ports Details                         | USB-C: 5V 3A (15W), 9V 3A (27W), 12V 3A (36W), 15V 3A (45W), 20V 3.25A (65W) |
| Charging Ports / Amps                          | (1) 3A                                                                       |
| Compatible Devices                             | Chromebook; Laptop; Smartphone; Tablet                                       |



Powering Business Worldwide



| PHYSICAL                            |                               |
|-------------------------------------|-------------------------------|
| Color                               | White                         |
| Material of Construction            | PC (Plastic)                  |
| Unit Dimensions (hwd / in.)         | 2.210 x 1.970 x 1.130         |
| Unit Dimensions (hwd / cm)          | 5.62 x 5.0 x 2.87             |
| Unit Packaging Type                 | Box                           |
| Unit Weight (lbs.)                  | 0.23                          |
| Unit Weight (kg)                    | 0.10                          |
| ENVIRONMENTAL                       |                               |
| Operating Temperature Range         | 32° to 104°F (0° to 40°C)     |
| Storage Temperature Range           | -4° to 185°F (-20° to 85°C)   |
| Operating Humidity Range            | 20 to 90 % RH, Non-Condensing |
| Storage Humidity Range              | 5 to 90 % RH, Non-Condensing  |
| FEATURES & SPECIFICATIONS           |                               |
| GaN Technology                      | Yes                           |
| Overcurrent Protection              | No                            |
| Overvoltage Protection              | No                            |
| Over Current Protection             | Yes                           |
| Quick Charge Compliant              | No                            |
| Driver Required                     | No                            |
| STANDARDS & COMPLIANCE              |                               |
| Product Certifications              | NOM (Mexico); UL Listed       |
| Product Compliance                  | RoHS; REACH; WEEE; FCC (USA)  |
| WARRANTY & SUPPORT                  |                               |
| Product Warranty Period (Worldwide) | 2-year limited warranty       |

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.