

https://www.phoenixcontact.com/us/products/1049498

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

DIN rail adapter, for NS 35 for accommodating two rows of PTFIX 1,5 distribution blocks, depth: 10.9 mm, width: 8 mm, height: 44.4 mm



### Commercial data

Item number	1049498
Packing unit	30 pc
Minimum order quantity	30 pc
Sales key	BE09
Product key	BEAZ11
Catalog page	Page 428 (C-1-2019)
GTIN	4055626650890
Weight per piece (including packing)	1.598 g
Weight per piece (excluding packing)	1.5 g
Customs tariff number	39269097
Country of origin	PL

PHŒNIX

1049498

https://www.phoenixcontact.com/us/products/1049498



### Technical data

#### Product properties

	Product type	Mounting material	
Dimensions			
	Width	8 mm	
	Height	44.4 mm	
	Depth	10.9 mm	

### Environmental and real-life conditions

Ambient conditions				
Ambient temperature (operation)	-60 °C 105 °C (max. short-term operating temperature RTI Elec.)			
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)			
Ambient temperature (assembly)	-5 °C 70 °C			
Ambient temperature (actuation)	-5 °C 70 °C			
Permissible humidity (storage/transport)	30 % 70 %			



https://www.phoenixcontact.com/us/products/1049498



### Classifications

#### ECLASS

ECLASS-11.0	27370419
ECLASS-12.0	27370419
ECLASS-13.0	27370419

#### ETIM

	ETIM 9.0	EC001024	
UNSPSC			
	UNSPSC 21.0	39121400	

1049498

https://www.phoenixcontact.com/us/products/1049498



### Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions	
China RoHS		
Environment friendly use period (EFUP)	EFUP-E	
	No hazardous substances above the limits	
EU REACH SVHC		
REACH candidate substance (CAS No.)	No substance above 0.1 wt%	



https://www.phoenixcontact.com/us/products/1049498



### Accessories

0

Note: Applying some accessories below might limit this product.

FBS 2-4 - Plug-in bridge

3030116 https://www.phoenixcontact.com/us/products/3030116



Plug-in bridge, pitch: 4.2 mm, number of positions: 2, color: red

17.5 A Max. current carrying capacity: 17.5 A

### FBS 2-4 GY - Plug-in bridge

3030118 https://www.phoenixcontact.com/us/products/3030118

Plug-in bridge, pitch: 4.2 mm, number of positions: 2, color: gray



17.5 A Max. current carrying capacity: 17.5 A

1049498

https://www.phoenixcontact.com/us/products/1049498



#### FBS 2-4 BU - Plug-in bridge

#### 3030117

https://www.phoenixcontact.com/us/products/3030117



Plug-in bridge, pitch: 4.2 mm, number of positions: 2, color: blue

Max. current carrying capacity: 17.5 A

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com