

1700024

https://www.phoenixcontact.com/us/products/1700024

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cover required at the end of a row of terminal blocks

Your advantages

- · Well-known connection principle allows worldwide use
- · Low temperature rise, thanks to maximum contact force
- · Allows connection of two conductors
- · Operation and conductor connection from one direction enable integration into front of device

Commercial data

Item number	1700024
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	AA18
Product key	AARZCA
Catalog page	Page 455 (CC-2007)
GTIN	4017918022716
Weight per piece (including packing)	0.608 g
Weight per piece (excluding packing)	0.606 g
Customs tariff number	85389099
Country of origin	PL



1700024

https://www.phoenixcontact.com/us/products/1700024

Technical data

Product properties

Product type	End cover
Product family	DECKEL + RZ + DP
Number of positions	0

Material specifications

Color (Housing)	green (RAL 6021)
Flammability rating according to UL 94	V0

Dimensions

Width	2.5 mm
Height	18.5 mm
Length	19.5 mm



1700024

https://www.phoenixcontact.com/us/products/1700024

Classifications

UNSPSC 21.0

ECLASS

ECLASS-	12.0	27460407
ECLASS-	13.0	27460407
ECLASS-	11.0	27460407
ETIM		
ETIM 9.0		EC002943
UNSPSC		

39121400



1700024

https://www.phoenixcontact.com/us/products/1700024

Environmental product compliance

EU R	oHS
------	-----

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



https://www.phoenixcontact.com/us/products/1700024



Accessories

FRONT 2,5-H/SA 5 - PCB terminal block

1700008

https://www.phoenixcontact.com/us/products/1700008



PCB terminal block, nominal current: 24 A, rated voltage (III/2): 400 V, nominal cross section: 2.5 mm², number of potentials: 1, number of rows: 1, number of positions per row: 1, product range: FRONT 2,5-H/SA 5, pitch: 5 mm, connection method: Front screw connection, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green, Pin layout: Linear pinning, Solder pin [P]: 3.5 mm, number of solder pins per potential: 2, type of packaging: packed in cardboard. The article can be aligned to create different nos. of positions!

RZ 2,5-FRONT 2,5 H - Pitch spacer

1700079

https://www.phoenixcontact.com/us/products/1700079



Pitch spacer, raises the pitch by 2.5 mm, interlocks with terminal block of the same shape, color: green

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com