

# P-DI GY - Isolating plugs



3047390  
<https://www.phoenixcontact.com/us/products/3047390>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Isolating plugs, depth: 23.1 mm, width: 3.5 mm, height: 10.8 mm, color: gray

## Your advantages

- Can be used in all ...-TG disconnect terminal blocks from the CLIPLINE complete system
- The P-DI isolating plug can be easily removed to release the connection and then "parked" back to front in the disconnect zone

## Commercial data

Item number	3047390
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BE29
Product key	BE2ZWX
GTIN	4046356140225
Weight per piece (including packing)	0.62 g
Weight per piece (excluding packing)	0.629 g
Customs tariff number	85366990
Country of origin	CN

# P-DI GY - Isolating plugs



3047390

<https://www.phoenixcontact.com/us/products/3047390>

## Technical data

### Product properties

Product type	Knife
--------------	-------

### Dimensions

Width	3.5 mm
Height	10.8 mm
Depth	23.1 mm

### Material specifications

Color	gray
Flammability rating according to UL 94	V2
Insulating material	PA
Static insulating material application in cold	-40 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

# P-DI GY - Isolating plugs


3047390


<https://www.phoenixcontact.com/us/products/3047390>




## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3047390>

	<b>CSA</b> Approval ID: 2030668			
	Nominal voltage U <sub>N</sub>	Nominal current I <sub>N</sub>	Cross section AWG	Cross section mm <sup>2</sup>
	-	15 A	-	-

	<b>EAC</b> Approval ID: RU C-DE.BL08.B.00511
---	---

	<b>BV</b> Approval ID: 25278/C1 BV
---	---------------------------------------

# P-DI GY - Isolating plugs



3047390  
<https://www.phoenixcontact.com/us/products/3047390>

## Classifications

### ECLASS

ECLASS-11.0	27141190
ECLASS-12.0	27141190
ECLASS-13.0	27141190

### ETIM

ETIM 9.0	EC002848
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# P-DI GY - Isolating plugs



3047390  
<https://www.phoenixcontact.com/us/products/3047390>

## Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)