9065SDO15

Overload Relay, Type S, melting alloy, replacement overload, NEMA size 4, 3 pole, 3 phase, 135A, 600VAC



Main

Range of Product	Replacement Relay
Product destination	Starter
Thermal overload type	Melting alloy

Complementary

o in promortiary		
NEMA size	4	
Phase	3 phase	
Number of thermal units required	3	
Mounting Support	Mounting plate	
[Ue] rated operational voltage	600 V AC	
Height	6.97 in (177 mm)	
Width	5.31 in (134.9 mm)	
Depth	5.74 in (145.8 mm)	

Ordering and shipping details

<u> 3 - - - - - - </u>	
Category	US10CP121661
Discount Schedule	0CP1
GTIN	785901850809
Returnability	Yes
Country of origin	US

Packing Units

•		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	6.30 in (16.002 cm)	
Package 1 Width	6.60 in (16.764 cm)	
Package 1 Length	8.50 in (21.59 cm)	
Package 1 Weight	3.30 lb(US) (1.497 kg)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	[™] China RoHS Declaration

Warranty 18 months