


# Product data sheet

## Characteristics

# 9065SDO8

Overload Relay, Type S, melting alloy, replacement overload, NEMA size 2, 3 pole, 3 phase, 45A, 600VAC



### Main

Range of Product	Replacement Relay
Product destination	Starter
Thermal overload type	Melting alloy

### Complementary

NEMA size	2
Phase	3 phase
Number of thermal units required	3
Mounting Support	Mounting plate
[Ue] rated operational voltage	600 V AC
Height	4.06 in (103.2 mm)
Width	4.28 in (108.7 mm)
Depth	4.00 in (101.6 mm)


### Ordering and shipping details

Category	US10CP121661
Discount Schedule	OCP1
GTIN	785901885238
Returnability	Yes
Country of origin	US

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.61 in (11.7 cm)
Package 1 Width	5.20 in (13.2 cm)
Package 1 Length	5.39 in (13.7 cm)
Package 1 Weight	16.96 oz (480.8 g)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

## Contractual warranty

---

Warranty	18 months
----------	-----------

---