# Product data sheet

Specifications





# Thermal overload relay, Easy TeSys DPER, 9-13A, class 10

DPER16

#### Main

Range	Easy TeSys
Product name	Easy TeSys DPER
product or component type	Thermal overload relay
Device short name	DPER
relay application	Overload protection
Product compatibility	Contactor DPE09-38
Thermal protection adjustment range	913 A
Thermal overload class	Class 10 IEC 60947-4-1
[Ui] rated insulation voltage	Power circuit 600 V cUL Power circuit 690 V IEC 60947-4-1

#### Complementary

Network type	DC AC
Network frequency	0400 Hz
Auxiliary contact composition	1 NO + 1 NC
[Ith] conventional free air thermal current	5 A signalling circuit
Permissible current	1.5 A 240 V AC-15 signalling circuit 0.1 A 250 V DC-13 signalling circuit
Phase failure sensitivity	Tripping current 130 % of Ir on two phase, the last one at 0
Tripping threshold	1.14 +/- 0.06 lr IEC 60947-4-1
Protection type	BS fuse 5 A control circuit GB2 circuit breaker 5 A control circuit GG fuse 5 A control circuit
[Ue] rated operational voltage	690 V AC 0400 Hz power circuit IEC 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV
Surge withstand	6 kV IEC 60801-5
Dielectric strength	1.89 kV 50 Hz IEC 60947-1
Control type	Red push-button stop Blue push-button reset
Mounting support	Separate, with specific accessories Under contactor

Connections - terminals	Control circuit screw clamp terminals 2 0.0020.004 in <sup>2</sup> (12.5 mm <sup>2</sup> ) flexible without cable end	
	Control circuit screw clamp terminals 2 0.0020.004 in <sup>2</sup> (12.5 mm <sup>2</sup> ) flexible with cable end	
	Control circuit screw clamp terminals 2 0.0020.004 in <sup>2</sup> (12.5 mm <sup>2</sup> ) solid without cable end Power circuit screw clamp terminals 1 0.000.01 in <sup>2</sup> (1.56 mm <sup>2</sup> ) flexible without cable end	
	Power circuit screw clamp terminals 1 0.0020.009 in <sup>2</sup> (16 mm <sup>2</sup> ) solid without cable end	
Tightening torque	Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals	
	Power circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals	
Height	2.6 in (66 mm)	
Width	1.8 in (45 mm)	
Depth	2.8 in (70 mm)	
net weight	0.273 lb(US) (0.124 kg)	

#### Environment

IP degree of protection	IP20 conforming to IEC 60529
Protective treatment	TH IEC 60068
Temperature compensation	-4140 °F (-2060 °C)
Ambient air temperature for operation	-4140 °F (-2060 °C) without derating IEC 60947-4-1
Ambient air temperature for storage	-76158 °F (-6070 °C)
Shock resistance	15 gn 11 ms IEC 60068-2-7
Vibration resistance	6 gn on plate IEC 60068-2-6
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CUL
Product certifications	cUL

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 in (5.0 cm)
Package 1 Width	3.07 in (7.8 cm)
Package 1 Length	3.5 in (9.0 cm)
Package 1 Weight	5.08 oz (144.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	5.9 in (15.0 cm)
Package 2 Width	11.8 in (30.0 cm)
Package 2 Length	15.7 in (40.0 cm)
Package 2 Weight	8.190 lb(US) (3.715 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	384

Package 3 Height	31.5 in (80.0 cm)
Package 3 Width	31.5 in (80.0 cm)
Package 3 Length	23.6 in (60.0 cm)
Package 3 Weight	151.616 lb(US) (68.772 kg)

Jul 1, 2024

Life Is On Scheider

### Sustainability Screen

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information