# LAD4RC3G D40A to D65A RC 50-127V Suppressor





#### Main

| Range                        | TeSys<br>TeSys Deca                |
|------------------------------|------------------------------------|
| Device short name            | LAD4                               |
| Product or Component<br>Type | Suppressor module                  |
| Product compatibility        | 3P LC1D40AD80A<br>4P LC1DT60ADT80A |

## Complementary

| Mounting location            | Front                 |  |
|------------------------------|-----------------------|--|
| Mounting Mode                | By clips              |  |
| Suppressor technology        | RC circuit            |  |
| [Uc] control circuit voltage | 50127 V AC            |  |
| Maximum peak voltage         | 3 Uc                  |  |
| Net Weight                   | 0.04 lb(US) (0.02 kg) |  |
| Color                        | Dark grey             |  |
|                              |                       |  |

#### Environment

| LITVITOTITICITE                       |                        |
|---------------------------------------|------------------------|
| Standards                             | IEC 60947-5-1          |
|                                       | EN 60947-5-1           |
|                                       | CSA C22.2 No 60947-5-1 |
|                                       | UL 60947-5-1           |
|                                       | GB/T 14048.5           |
| Product Certifications                | UL[RETURN]CSA          |
| IP degree of protection               | IP2XIEC 60529          |
| Ambient air temperature for operation | -13131 °F (-2555 °C)   |
| Ambient Air Temperature for Storage   | -40176 °F (-4080 °C)   |

### Ordering and shipping details

| Category          | US10I1222341  |  |
|-------------------|---------------|--|
| Discount Schedule | 0112          |  |
| GTIN              | 3389119410175 |  |
| Returnability     | Yes           |  |
| Country of origin | CZ            |  |

#### **Packing Units**

| Unit Type of Package 1       | PCE                 |  |
|------------------------------|---------------------|--|
| Number of Units in Package 1 | 1                   |  |
| Package 1 Height             | 0.98 in (2.500 cm)  |  |
| Package 1 Width              | 2.76 in (7.000 cm)  |  |
| Package 1 Length             | 3.94 in (10.000 cm) |  |
| Package 1 Weight             | 0.56 oz (16.000 g)  |  |
| Unit Type of Package 2       | BB1                 |  |
| Number of Units in Package 2 | 10                  |  |

| Package 2 Height             | 2.87 in (7.300 cm)     |
|------------------------------|------------------------|
| Package 2 Width              | 2.52 in (6.400 cm)     |
| Package 2 Length             | 5.12 in (13.000 cm)    |
| Package 2 Weight             | 6.46 oz (183.000 g)    |
| Unit Type of Package 3       | S01                    |
| Number of Units in Package 3 | 100                    |
| Package 3 Height             | 5.91 in (15.000 cm)    |
| Package 3 Width              | 5.91 in (15.000 cm)    |
| Package 3 Length             | 15.75 in (40.000 cm)   |
| Package 3 Weight             | 4.45 lb(US) (2.018 kg) |
|                              |                        |

# Offer Sustainability

| © REACh Declaration  Yes  Compliant □ EU RoHS Declaration  |
|--|
|  |
| Compliant EPEU RoHS Declaration  |
|  |
| Yes  |
| Yes  |
| ☑ China RoHS Declaration   |
| ₫Yes   |
| Product Environmental Profile  |
| No need of specific recycling operations   |
| The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
|  |

### Contractual warranty

| Warranty | 18 months |
|----------|-----------|
|          |           |