

LR9G630

Thermal overload relay, electronic, TeSys
Giga, 160A to 630A, Class 5E to 30E, push-in
control connection



Main

Range	TeSys
Product name	TeSys LRG
Product or Component Type	Electronic thermal overload relay
Device short name	LR9G
Relay application	Motor protection
Network type	AC
Thermal overload class	Class 5E...30E IEC 60947-4-1
Thermal protection adjustment range	160...630 A

Complementary

Network Frequency	30...60 Hz 100 Hz
Overvoltage category	III
Tripping threshold	1.125 +/- 0.07 In IEC 60947-4-1
Protection type	Ground fault protection 0...1 s - alarm circuit IEC 60947-4-1 Ground fault protection 0...1 s - alarm circuit UL 60947-4-1 Phase loss 0...4 s - alarm circuit Phase imbalance 0...5 s - alarm circuit IEC 60947-4-1 Phase imbalance 0...5 s - alarm circuit UL 60947-4-1
Local signalling	LED Trip indicator
Contacts type and composition	1 NO + 1 NC
[Ith] conventional free air thermal current	5 A
[Uc] control circuit voltage	24...500 V AC 50/60 Hz 24...250 V DC
[Ue] rated operational voltage	1000 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
Reset	Automatic reset Manual
Mechanical durability	7000 cycles
Surge withstand	4 kV
Electromagnetic compatibility	EMC immunity conforming to IEC 60947-4-1 Emission tests criteria A conforming to IEC 60947-4-1 Immunity to radiated radio-electrical interference - test level: 20 V/m conforming to EN/IEC 61000-4-3 Voltage dips and interruptions immunity test conforming to SEMI F47
Connections - terminals	Power circuit: bar - busbar cross section: 50 x 10 mm Power circuit: lugs-ring terminals 1 0.47 in ² (300 mm ²) Control circuit: push-in 1 0.00...0.00 in ² (0.2...2.5 mm ²) - cable stiffness: solid stranded without cable end Control circuit: push-in 1 0.00...0.00 in ² (0.25...2.5 mm ²) - cable stiffness: flexible with cable end Control circuit: push-in 2 0.00...0.00 in ² (0.5...1.0 mm ²) with cable end
Tightening torque	58 N.m
Mounting support	Direct on contactor Plate

Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 JIS C8201-5-1
Product Certifications	CB Scheme[RETURN]CCC[RETURN]cULus[RETURN]UKCA[RETURN]ATEX[RETURN]EU-RO-MR by DNV-GL[RETURN]EAC

Environment

IP degree of protection	IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106
Protective treatment	TH
Ambient air temperature for operation	-13...140 °F (-25...60 °C)
Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)
Permissible ambient air temperature around the device	-40...140 °F (-40...60 °C) at Uc
Adjustment of dial setting	-13...140 °F (-25...60 °C)
Mechanical robustness	Vibrations 5...300 Hz 6 gn contactor open Shocks 15 gn 11 ms contactor closed
Height	5.83 in (148 mm)
Width	8.31 in (211 mm)
Depth	7.32 in (186 mm)
Net Weight	5.89 lb(US) (2.67 kg)
Color	Dark grey






Ordering and shipping details

Category	US10I1222330
Discount Schedule	0I12
GTIN	3606481912589
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.81 in (30 cm)
Package 1 Width	11.81 in (30 cm)
Package 1 Length	15.75 in (40 cm)
Package 1 Weight	10.28 lb(US) (4.665 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product