



Main

Range	TeSys
Product or Component Type	Contacteur coil
Device short name	LX1G
Poles description	3P
Range compatibility	TeSys G LX1G contactor coil
Product Compatibility	LC1G265...330
[Uc] control circuit voltage	100...250 V AC/DC 50/60 Hz
Operating time	20...35 ms opening 40...55 ms closing
Mechanical durability	5 Mcycles
Maximum operating rate	600 cyc/mn 140 °F (60 °C)

Complementary

Coil technology	Built-in bidirectional peak limiting
Control circuit voltage limits	Operational 0.8...1.1 Uc 140 °F (60 °C) Drop-out 0...0.45 Uc 140 °F (60 °C)
Connections - terminals	Control circuit push-in termination 1 0.00...0.00 in ² (0.2...2.5 mm ²) solid stranded without cable end sleeve AWG 26...AWG 12 Control circuit push-in termination 1 0.00...0.00 in ² (0.25...2.5 mm ²) flexible with cable end sleeve AWG 24...AWG 14 Control circuit push-in termination 2 0.00...0.00 in ² (0.5...1.0 mm ²) rigid or stranded with cable end sleeve AWG 20...AWG 18
Inrush power in VA	840 VA 240 V AC, 60 Hz
Inrush power in W	645.0 W DC
Hold-in power consumption in VA	10.6 VA 240 V AC, 60 Hz
Hold-in power consumption in W	5.9 W DC

Environment

IP degree of protection	IP20 IEC 60529
Operating altitude	9842.52 ft (3000 m) without derating 5000 m with derating factor
Electromagnetic compatibility	EMC immunity conforming to IEC 60947-4-1 Emission tests criteria A conforming to IEC 60947-4-1 Immunity to radiated radio-electrical interference - test level: 20 V/m conforming to EN/IEC 61000-4-3 Voltage dips and interruptions immunity test conforming to SEMI F47
Standards	EN/IEC 60947-4-1 UL 60947-4-1A CSA C22.2 No 60947-4-1
Pollution degree	3 IEC 60947-1
Ambient Air Temperature for Operation	-13...140 °F (-25...60 °C)
Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)
Permissible ambient air temperature around the device	-40...158 °F (-40...70 °C) at Uc
Height	6.57 in (167.0 mm)
Width	5.51 in (140.0 mm)
Depth	3.66 in (93.0 mm)
Quantity per Set	1

Ordering and shipping details

Category	US10I1222328
Discount Schedule	0I12
GTIN	03606481946317
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.69 in (17.0 cm)
Package 1 Width	9.45 in (24.0 cm)
Package 1 Length	8.66 in (22.0 cm)
Package 1 Weight	4.41 lb(US) (2.0 kg)
Unit Type of Package 2	S03
Number of Units in Package 2	2
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	10.14 lb(US) (4.6 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product