LXD1U7

TeSys D, replaement coil, for LC1D09 to 38 contactors and CAD relays, 240 VAC 50/60 Hz coil





Main

Range	TeSys
Product or Component Type	Contactor coil
Device short name	LXD1
Control circuit type	AC 50/60 Hz
[Uc] control circuit voltage	240 V AC 50/60 Hz
Average resistance	562.3 Ohm 68 °F (20 °C)
Inductance of closed circuit	22 H
Product Compatibility	CAD LC1DT20DT40 LC1D09D38
Mechanical durability	15 Mcycles
Maximum operating rate	3600 cyc/h 140 °F (60 °C)

Complementary

Coil technology	Without built-in suppressor module	
Control circuit voltage limits	Drop-out: 0.30.6 Uc at 50/60 Hz (at <140 °F (60 °C)) Operational: 0.81.1 Uc at 50 Hz (at <140 °F (60 °C)) Operational: 0.851.1 Uc at 60 Hz (at <140 °F (60 °C))	
Inrush power in VA	70 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C)) 70 VA 50 Hz cos phi 0.75 (at 68 °F (20 °C))	
Hold-in power consumption in VA	7.5 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C)) 7 VA 50 Hz cos phi 0.3 (at 68 °F (20 °C))	
Heat dissipation	23 W 50/60 Hz	

Environment

Ambient Air Temperature for Operation	23140 °F (-560 °C)
Net Weight	0.15 lb(US) (0.07 kg)

Ordering and shipping details

Category	US10I1222341	
Discount Schedule	0112	
GTIN	3389110467949	
Returnability	Yes	
Country of origin	US	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.77 in (4.500 cm)	
Package 1 Width	2.48 in (6.300 cm)	
Package 1 Length	1.57 in (4.000 cm)	
Package 1 Weight	2.61 oz (74.000 g)	
Unit Type of Package 2	S02	

Number of Units in Package 2	100	
Package 2 Height	5.91 in (15.000 cm)	
Package 2 Width	11.81 in (30.000 cm)	
Package 2 Length	15.75 in (40.000 cm)	
Package 2 Weight	17.08 lb(US) (7.748 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months