



Main

Product or Component Type	Power cable
Accessory / separate part type	Preassembled power cordset
Accessory / separate part category	Connection accessory
Product compatibility	Servo motor BMH, 1 7.48 in (190 mm))E IEC 60204-1 Servo motor BMH, 3 8.07 in (205 mm))E IEC 60204-1 Servo motor BSH, 2 5.51 in (140 mm)) Servo motor BSH, 3 5.51 in (140 mm)) Servo motor BSH, 4 5.51 in (140 mm))
Accessory / separate part destination	Between servo motor and servo drive
Range Compatibility	Lexium 15 Lexium 32 Lexium 05
Cable length	32.81 ft (10 m)
Cable composition	4 x 4 mm ² + 2 x 1 mm ²

Complementary

Electrical connection	Free end servo drive side Connector - industrial M40 servo motor side
Net Weight	9.11 lb(US) (4.13 kg)

Ordering and shipping details

Category	US1PC5118263
Discount Schedule	PC51
GTIN	3389119207416
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.11 in (7.900 cm)
Package 1 Width	17.17 in (43.600 cm)
Package 1 Length	17.60 in (44.700 cm)
Package 1 Weight	10.24 lb(US) (4.644 kg)
Unit Type of Package 2	P06
Number of Units in Package 2	18
Package 2 Height	29.53 in (75.000 cm)
Package 2 Width	23.62 in (60.000 cm)
Package 2 Length	31.50 in (80.000 cm)
Package 2 Weight	215.09 lb(US) (97.564 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------