VW3M5105R100

power cable - between servomotor BSH and servodrive - 4 x 6 mm² + 2 x 1 mm² -10m





Main

Product or Component Type	Power cable
Accessory / separate part type	Preassembled power cordset
Accessory / separate part categor	Connection accessory
Product compatibility	Servo motor BMH, 1 7.48 in (190 mm))B2 IEC 60204-1 Servo motor BMH, 2 7.48 in (190 mm))E IEC 60204-1 Servo motor BMH, 3 7.48 in (190 mm))E IEC 60204-1 Servo motor BMH, 3 8.07 in (205 mm))B2 IEC 60204-1
Accessory / separate part destination	Between servo motor and servo drive
Range Compatibility	Lexium 32
Cable length	32.81 ft (10 m)
Cable composition	4 x 6 mm² + 2 x 1 mm²

Complementary

Electrical connection	Free end servo drive side Connector - industrial M40 servo motor side
Net Weight	14.33 lb(US) (6.5 kg)

Ordering and shipping details

Category	US1PC5118263
Discount Schedule	PC51
GTIN	3606485263878
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	5.91 in (15.0 cm)	
Package 1 Width	19.69 in (50.0 cm)	
Package 1 Length	19.69 in (50.0 cm)	
Package 1 Weight	14.16 lb(US) (6.424 kg)	
Unit Type of Package 2	S06	
Number of Units in Package 2	16	
Package 2 Height	28.94 in (73.5 cm)	
Package 2 Width	23.62 in (60.0 cm)	
Package 2 Length	31.50 in (80.0 cm)	
Package 2 Weight	255.26 lb(US) (115.784 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
PVC free	Yes

Contractual warranty

Contraction warranty	
Warranty	18 months