VW3M5501R50

power cordset 4x1,5mm² + 2x1mm² + 2x0,14mm² 5 m one end w M23 industrial con.





Main

Range of Product	Altivar
Accessory / separate part type	Power cable
Accessory / separate part categor	Connection accessories
Accessory / separate part destination	Between synchronous motor and variable speed drive
Range Compatibility	Altivar Machine ATV320 Altivar 32
Cable length	16.40 ft (5 m)
Type of Cable	Shielded cable

Complementary

Product compatibility	Synchronous motor BMP 5.51 in (140 mm), 1 C	
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Synchronous motor BMP 5.51 in (140 mm), 1 F	
	Synchronous motor BMP 5.51 in (140 mm), 2 C	
	Synchronous motor BMP 2.76 in (70 mm), 1 R	
	Synchronous motor BMP 2.76 in (70 mm), 1 F	
	Synchronous motor BMP 2.76 in (70 mm), 2 R	
	Synchronous motor BMP 2.76 in (70 mm), 2 F	
	Synchronous motor BMP 3.94 in (100 mm), 1 R	
	Synchronous motor BMP 3.94 in (100 mm), 1 F	
	Synchronous motor BMP 3.94 in (100 mm), 2 R	
	Synchronous motor BMP 3.94 in (100 mm), 2 F	
Electrical connection	1 connector M23 8 synchronous motor side	
	1 free end variable speed drive side	
Cable composition	4 x 1.5 mm ² + 2 x 1 mm ² + 2 x 0.14 mm ²	
Net Weight	2.80 lb(US) (1.27 kg)	

Ordering and shipping details

Category	US1PC5118263	
Discount Schedule	PC51	
GTIN	3606480564529	
Returnability	No	
Country of origin	CZ	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.36 in (6.0 cm)	
Package 1 Width	8.27 in (21.0 cm)	
Package 1 Length	9.06 in (23.0 cm)	
Package 1 Weight	3.15 lb(US) (1.43 kg)	
Unit Type of Package 2	S04	
Number of Units in Package 2	5	
Package 2 Height	11.81 in (30.0 cm)	
Package 2 Width	15.75 in (40.0 cm)	
Package 2 Length	23.62 in (60.0 cm)	
Package 2 Weight	18.63 lb(US) (8.452 kg)	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability of these products for specific user applications. This characteristic is not integrated to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
PVC free	Yes

Contractual warranty

Contraction warranty	
Warranty	18 months