
Strain relief housing; 5-pole; for 2 cables; 9.0 ... 13.0 mm; 55 mm; black

www.wago.com/770-505







Item description

Strain relief housing WINSTA® MIDI 5-pole

The strain relief housing from the *WINSTA*® MIDI product line guarantees you the greatest flexibility in electrical installation. With WAGO, you benefit from a large selection of accessories for the WINSTA® product line. The *WINSTA*® MIDI product line achieves total flexibility for the installation. Through its Push-in CAGE CLAMP® spring pressure connection technology, it ensures error-free, time-saving installation and offers flexibility for meeting all installation requirements. The strip length is 55 mm.

Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

The WINSTA® Pluggable Connection System is perfectly tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and thus more efficient, even more reliable, and error-free. Using this pre-assembled system decreases time spent on assembly and errors during installation at the construction site. Now you can also lower installation expenses without compromising quality and

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/770-505



safety: with protection against mismating eliminates the need for servicing and prevents unnecessary downtime.

- simple circuits
- convenient installation and commissioning

Data

Connection data

Connection 1

Pole number	5
Connectable sheathed cable diameter	9 13 mm
Strip length (outer insulation)	55 mm

Physical data

Width	54.6 mm / 2.15 inches
Height	17 mm / 0.669 inches
Depth	50 mm / 1.969 inches

Material data

Note (material data)

Information on material specifications can be found here

Color	black
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	VO
Fire load	0.376 MJ
Weight	13 g

Environmental requirements

Processing temperature	-5 +40 °C
Continuous operating temperature	-35 +85 ℃
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



Commercial data

Product Group	20 (Winsta)
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 8.0	EC002863
ETIM 7.0	EC002863
ECCN	NO DATA
PU (SPU)	25 pcs
Packaging type	box
Country of origin	DE
GTIN	4017332701679
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
c 911 °us	cURus Underwriters Laboratories Inc.	UL 1977	E45171
c FLL us	cURus Underwriters Laboratories Inc.	UL 1059	E 45172
\sim	VDE VDE Prüf- und Zertifizierungsinstitut	EN 61535	40029808



Approvals for marine applications

	DNV GL	-	TAE00001Z6
Logo	Approval	Additional Approval Text	name
			Certificate

Det Norske Veritas, Germanischer Lloyd

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27

32423 Minden Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/770-505







LR Lloyds Register IEC 61984

LR22429487TA

Optional accessories

Marking accessories

Marking strip



Item no.: 210-333

Marking strips; as a DIN A4 sheet; Strip width 6 mm; Strip length 182 mm; plain; Self-adhesive; white

www.wago.com/210-333

Downloads

Documentation

Bid Text

770-505 X81 - Datei	2019 年2月19 日	xml 2.8 kB	Download
770-505 doc - Datei	2015 年3月12 日	doc 24.1 kB	Download
ausschreiben.de 770-505		URL	Download

CAD/CAE-Data

2D/3D Models 770-505

CAD data

CAE data		
EPLAN Data Portal 770-505	URL	Download
WSCAD Universe 770-505	URL	Download

ZUKEN Portal 770-505

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

URL

Download

www.wago.com/770-505



URL Download

Asset Administration Shell

Asset Administration Shell 770-505 URL Download

Environmental Product Compliance

Compliance Search

URL **Environmental Product Compliance 770-505** Download

Strain relief housing; 5-pole; for 2 cables; 9.0 ... 13.0 mm; 55 mm; black

Installation Notes

Product family

WINSTA® MIDI

Show all products from the family

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.