




# Guided actuators DFM-16-80-P-A-KF-F1A

Part number: 8118836

**FESTO**



 [General operating condition](#)

## Data sheet

| Feature   | Value   |
|---|---|
| Distance of centre of gravity of payload to yoke plate xs | 50 mm   |
| Stroke  | 80 mm   |
| Piston diameter   | 16 mm   |
| Drive unit operating mode                                 | Yoke  |
| Cushioning  | Elastic cushioning rings/pads at both ends  |
| Mounting position   | Any   |
| Guide   | Recirculating ball bearing guide  |
| Structural design   | Guide   |
| Position sensing  | For proximity sensor  |
| Symbol  | 00991737  |
| Variants  | Metals with copper, zinc or nickel as main constituent are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils.            |
| Operating pressure  | 0.2 MPa ... 1 MPa   |
| Operating pressure  | 2 bar ... 10 bar  |
| Max. speed  | 0.8 m/s   |
| Mode of operation   | Double-acting   |
| Operating medium  | Compressed air as per ISO 8573-1:2010 [7:4:4]   |
| Information on operating and pilot media                  | Operation with oil lubrication possible (required for further use)  |
| Corrosion resistance class (CRC)                          | 0 - No corrosion stress   |
| LABS (PWIS) conformity                                    | VDMA24364-B1/B2-L   |
| Suitability for the production of Li-ion batteries        | Metals with more than 1% by mass of copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils |
| Cleanroom class   | Class 7 according to ISO 14644-1  |
| Ambient temperature                                       | -5 °C ... 60 °C   |
| Impact energy in the end positions                        | 0.15 J  |
| Max. force Fy   | 778 N   |
| Max. force Fy static                                      | 830 N   |
| Max. force Fz   | 778 N   |
| Max. force Fz static                                      | 830 N   |
| Max. torque Mx  | 17.9 Nm   |
| Max. static moment Mx                                     | 19.09 Nm  |
| Max. torque My  | 10.5 Nm   |
| Max. static moment My                                     | 11.2 Nm   |
| Max. torque Mz  | 10.5 Nm   |

| Feature  | Value                      |
|--|----------------------------|
| Max. static moment Mz  | 11.2 Nm                    |
| Max. permissible torque load Mx as a function of the stroke      | 2.03 Nm                    |
| Max. payload as a function of the stroke at defined distance xs  | 64 N                       |
| Theoretical force at 6 bar, retracting                           | 90 N                       |
| Theoretical force at 6 bar, advancing                            | 121 N                      |
| Moving mass  | 359 g                      |
| Product weight   | 872 g                      |
| Center of gravity of the moving mass as a function of the stroke | 47.8 mm                    |
| Alternative connections  | See product drawing        |
| Pneumatic connection   | M5                         |
| Note on materials  | RoHS-compliant             |
| Cover material   | Wrought aluminum alloy     |
| Seals material   | NBR                        |
| Housing material   | Wrought aluminum alloy     |
| Piston rod material  | High-alloy stainless steel |