

USB C Multiport Adapter - USB-C Travel Dock to 4K HDMI, 3x USB 3.0 Hub, SD/SDHC, GbE, 60W PD 3.0 Pass-Through - Portable USB-C Mini Docking Station USB Type-C/Thunderbolt 3

Product ID: DKT30CSDHPD3



This USB-C multiport adapter with HDMI turns your MacBook Pro, Dell XPS, or other USB-C laptop into a workstation, anywhere you go. The USB Type-C multiport adapter provides 4K HDMI video output, a USB Type-C port (data/power), two USB 3.0 Type-A ports, a Gigabit Ethernet port and an SD card reader slot, all through one connection to your laptop's USB-C or Thunderbolt 3 port. Plus, it offers advanced charging through USB Power Delivery 3.0.

The portable docking station connects your laptop to a 4K HDMI monitor (4096 x 2160p) to create a powerful workstation. It can also connect to an ultrawide monitor.

The USB-C to USB 3.0 hub gives you one USB-C port and two USB-A ports to connect your latest and legacy USB devices.

Access your multimedia content with ease. The multiport adapter provides direct access to your SD, SDHC and SDXC memory cards or microSD cards (with adapter, sold separately).

With support for USB PD 3.0 (up to 60W), the USB Type-C multiport adapter lets you power and charge your laptop, and power your peripherals when connected to a USB-C power adapter. PD 3.0 features Fast Role Swap to prevent USB data disruption when you switch power sources (USB-C power adapter to bus power).

The Gigabit Ethernet port ensures reliable wired network access.

The DKT30CSDHPD3 is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Note: To ensure full adapter functionality, your laptop's USB-C port must support USB Power Delivery and DP Alt Mode.

## **Certifications, Reports and Compatibility**





## **Applications**

- Ideal for meetings and making presentations in the boardroom
- Transfer photos, videos or other files from your SD cards to your USB-C laptop, tablet or other device
- Use an HDMI port-equipped television in a hotel room as an external display
- Power the adapter and your laptop through USB-C, using your laptop's power adapter
- Ideal for small workspaces in offices, home offices as well as office hoteling

## **Features**

- USB-C MULTIPORT ADAPTER: Portable USB C travel docking station with 4K 30Hz HDMI video output; aluminum space gray design complements Macbook Air, MacBook Pro, Dell XPS, HP EliteBook laptops
- 6-IN-1 USB-C HUB: This USB C multiport adapter features 4K HDMI (UHD), 2x USB-A 3.0 (5Gbps) and 1x USB-C (Data or Power Delivery 3.0 Pass Through), SD / SDHC / SDXC card reader slot & Gigabit Ethernet
- 60W PD 3.0 PASS THROUGH: Use a USB-C power adapter to charge laptop (up to 48W) & power the dock (12W); Prevents USB device drop out when the power is added/removed on PD 3.0 laptops like MacBook Pro
- WIDE DEVICE COMPATIBILITY: USB-C mini dock works w/ Thunderbolt 3 (TB3) laptops/ultrabooks; USB-C laptops, ultrabooks, chromebooks, tablets & phones for brands like MacBook, HP, Dell, Lenovo, Surface
- WIDE OS COMPATIBILITY & EASY SETUP: This USB Type-C Multiport adapter has automatic driver installation & supports Windows, macOS, Chrome OS and Android; ideal for business travel and work from home

Hardware			
	Warranty	3 Years	
	4K Support	Yes	
	Fast-Charge Port(s)	No	





Displays Supported

Bus Type USB-C

Industry Standards IEEE 802.3, IEEE 802.3u, IEEE 802.3ab

USB 3.0 - Backward compatible with USB 2.0 and 1.1

Chipset ID VIA/VLI - VL102

VIA Labs - VL163

VIA/VLI - VL817

Genesys Logic - GL823K

Parade - PS176

Realtek - RTL8153

**Performance** 

Maximum Data Transfer

Rate

Maximum Digital Resolutions

4096 x 2160p @ 24Hz or 3840 x 2160p (HDMI) @ 30Hz<br/>>

UltraWide - 3440 x 1440p @ 60 Hz or 2560x1080 at 60Hz

Lower resolutions are also supported. For example, if the max is  $3840 \times 2160p$  (4K), it also supports  $2560 \times 1600p$  and  $2560 \times 1600p$  and 256

1440p.

Type and Rate USB 3.0 - 5 Gbit/s

UASP Support Yes

Memory Media Type Secure Digital Card

SDHC (Secure Digital High Capacity)

SDXC (Secure Digital eXtended Capacity)

microSD (Micro Secure Digital) (adapter required)

microSDHC (Micro Secure Digital High Capacity) (adapter

required)

microSDXC (Micro Secure Digital eXtended Capacity) (adapter

required)





Compatible Networks 10/100/1000 Mbps

Auto MDIX Yes

Full Duplex Support Yes

Connector(s)

Connector Type(s) 1 - USB 3.2 Type-C (24 pin, Gen 1, 5Gbps)

1 - HDMI (19 pin)

1 - RJ-45

2 - USB Type-A (9 pin, 5 Gbps)

1 - SD Slot

1 - USB 3.2 Type-C (24 pin, Gen 1, 5Gbps)

**Software** 

OS Compatibility Windows 7, 8, 8.1, 10, 11<br/>
br / >macOS 10.11 to 10.15, 11.0,

12.0, 13.0, 14.0<br / >Android<br / >Chrome OS

Special Notes / Requirements

System and Cable Requirements

A host laptop with an available USB-C port (to ensure full adapter functionality, the host USB-C port must support USB

Power Delivery 2.0 and DP alt mode)

Optional: USB-C power adapter (for example, your laptop's

USB-C based power adapter)

Note

Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure that your host USB-C port supports

USB Power Delivery 2.0 or higher and DP alt mode.

The adapter can connect to a host laptop's USB-C port that doesn't support USB Power Delivery 2.0. However, in this configuration if a power adapter is connected to the multifunction adapter, it will not pass power through to your host laptop.

A 4K-capable display is required to achieve 3840 x 2160p resolution (4K is also known as 4K x 2K)

USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps.

Your laptop might have specific charging requirements. For example, if your laptop requires exactly 60W of power and an adapter consumes some of the 60W, your laptop might not recognize that it is getting enough power. For more information



about Power Delivery, refer to the manufacturer of your hardware.

**Power** 

Power Source USB-Powered

Power Delivery 60W

Output Voltage 5 DC

**Environmental** 

Operating Temperature 0C to 45C (32F to 113F)

Storage Temperature -10C to 85C (14F to 185F)

Humidity 5~90% RH (Non-condensing)

Physical Characteristics

Color Space Gray

Material Aluminum

Cable Length 6.0 in [152 mm]

Product Length 10.6 in [27.0 cm]

Product Width 1.8 in [4.5 cm]

Product Height 0.6 in [1.5 cm]

Weight of Product 3.0 oz [85.0 g]

Packaging Information

Package Quantity 1

Package Length 6.8 in [17.2 cm]

Package Width 5.7 in [14.4 cm]

Package Height 1.3 in [3.2 cm]

Shipping (Package) 5.5 oz [156.0 g]

Weight

What's in the Box

Included in Package 1 - multiport adapter



## 1 - quick-start guide

\*Product appearance and specifications are subject to change without notice.