

A770MS337M1VLAS022 A770, Polymer Aluminum, 330 uF, 20%, 35 VDC, -55/+125°C

A770

SMD Can

General Information

Rated Temperature

Ripple Current

Leakage Current High Temperature Solder

Life


ESR

Series

Style

Dielectric

Description



0.2 Maximum

	RoHS	Yes	
R	Lead	V-Chip	
	Qualifications	AEC-Q200	1
	AEC-Q200	Yes	
	Halogen Free	Yes	
	Specifications		
	Capacitance		330 uF
	Capacitance Tolerance		20%
	Voltage DC		35 VDC
	Temperature Range		-55/+125°C

125°C 2000 Hrs

Yes

22 mOhms (100kHz 20C)

346.5 uA (2min 20°C)

2200 mAmps (100kHz 125C)

Polymer Aluminum

Surface Mount, Polymer Aluminum

Dimensions	
D	10mm +/-0.5mm
L	12.2mm +/-0.3mm
W	10.3mm +/-0.2mm
Н	10.3mm +/-0.2mm
С	11mm +/-0.2mm
Р	4.6mm NOM
R	0.8 - 1.1mm

Packaging Specifications Packaging

T&R, 380mm

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.