



40 dB Fixed Attenuator, N Male to N Female Directional Black Aluminum Heatsink Body Rated to 1000 Watts Up to 2.5 GHz

RF Fixed Attenuators Technical Data Sheet

PE7423-40

Features

- Directional
- DC to 2.5 GHz Frequency Range
- Attenuation 40±1.5 dB
- Max Power 1 kW (CW)
- VSWR < 1.35:1

Applications

- Instrumentation
- Precision measurements
- Prototyping and characterization
- Production systems

Description

Pasternack carries a wide range of fixed attenuators with a broad selection of attenuation levels, frequency ranges, and power dissipation ranges. RF microwave attenuators (also known as RF pads) lower the amplitude of a signal (attenuate) a known amount and can be used in a wide variety of applications. These attenuator pads are used when a signal needs to be reduced to protect measurement equipment or other circuitry, to extend the range of power meters and amplifiers, and to impedance match circuits by reducing the VSWR seen by adjacent components. RF attenuators can prevent signal overload in amplifiers, receivers and detectors, adjusting the signal level to a range that is optimal.

Few RF components are as commonly used as fixed coaxial attenuators, and Pasternack carries one of the largest in-stock varieties and ships them same day. The 40 dB Fixed Attenuator PE7423-40 is rated to 1000 Watts and operates from DC to 2.5 GHz. The versatile coaxial package uses type N male to type N female connectors and is also REACH and RoHS compliant. The Black Aluminum Heatsink body allows for efficient heat dissipation under high power usage conditions.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		2.5	GHz
Impedance		50		Ohms
Nominal Attenuation		40		dB
Attenuation Accuracy		±1.5		dB
VSWR			1.35:1	
Input Power, CW derated linearly to 100W at +125°C			1	KWatts
Input Power, Peak 5µs pulse, 0.5% duty cycle			10	KWatts

Electrical Specification Notes:
 Power sensitivity 0.0001 dB/W max.
 Temperature coefficient 0.0004 dB/°C max.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [40 dB Fixed Attenuator, N Male to N Female Directional Black Aluminum Heatsink Body Rated to 1000 Watts Up to 2.5 GHz PE7423-40](#)



40 dB Fixed Attenuator, N Male to N Female Directional Black Aluminum Heatsink Body Rated to 1000 Watts Up to 2.5 GHz

RF Fixed Attenuators Technical Data Sheet

PE7423-40

Mechanical Specifications

Size

Length	14.8 in [375.92 mm]
Width/Diameter	8.95 in [227.33 mm]
Height	10.27 in [260.86 mm]
Weight	43 lbs [19.5 Kg]
Body Material and Plating	Black Aluminum Heatsink

Configuration

Design	Fixed, Directional
Package Style	Connectorized Module

Connectors

Description	Connector 1	Connector 2
Type	N Male	N Female
Connector Specification	MIL-STD-348A	MIL-STD-348A
Coupling Nut Material and Plating	Passivated Stainless Steel	
Body Material and Plating	Passivated Stainless Steel	Passivated Stainless Steel

Environmental Specifications

Temperature

Operating Range	-55 to +125 deg C
-----------------	-------------------

Environmental Specification Notes:
 Designed to meet MIL-DTL-3933 environmental specifications.

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:


40 dB Fixed Attenuator, N Male to N Female Directional Black Aluminum Heatsink Body Rated to 1000 Watts Up to 2.5 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [40 dB Fixed Attenuator, N Male to N Female Directional Black Aluminum Heatsink Body Rated to 1000 Watts Up to 2.5 GHz PE7423-40](#)

URL: <https://www.pasternack.com/40db-fixed-n-male-n-female-1000-watts-attenuator-pe7423-40-p.aspx>

PE7423-40 CAD Drawing

40 dB Fixed Attenuator, N Male to N Female Directional Black Aluminum Heatsink Body Rated to 1000 Watts Up to 2.5 GHz



STANDARD TOLERANCES	
.XX	±0.01
.XXX	±0.003

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

P/N	ATTEN.
PE7421-30	30 dB
PE7421-40	40 dB

DWG TITLE

PE7423

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].

PE PASTERNAK®
 THE ENGINEER'S RF SOURCE
 Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623
 Phone: (949) 261-1920 | Fax: (949) 261-7451
 Website: www.pasternack.com | E-Mail: sales@pasternack.com

CAGE CODE 53919

CAD FILE 121416

SCALE N/A

SIZE A

2233