3-1393303-7 ACTIVE

Power Relay F

TE Internal #: 3-1393303-7

Mini Relays, 24VDC Coil Voltage Rating, 30 - 50A Contact Current Class, Contact Arrangement 1 Form A (NO), Socket, 324Ω Coil

Resistance, Power Relay F

View on TE.com >



Relays & Contactors > Relays > Automotive Relays > Automotive Plug-In Relays > Mini Relays



Coil Voltage Rating: 24 VDC

Contact Current Class: 30 - 50 A

Contact Arrangement: 1 Form A (NO)

Product Mount Type: Socket

Coil Resistance: 324 Ω

Features

Configuration Features

Contact Arrangement 1 Form A (NO) Electrical Characteristics Contact Limiting Short-Time Current 240 A Contact Limiting Continuous Current 60 A Current Rating (85°C) 20 A Insulation Initial Dielectric Between Open Contacts 500 Vrms Contact Limiting Making Current 120 A Insulation Initial Dielectric Between Contacts & Coil 500 Vrms Contact Limiting Breaking Current 20 A Contact Limiting Breaking Current 20 A Contact Voltage Rating 24 VDC
Contact Limiting Short-Time Current Contact Limiting Continuous Current 60 A Current Rating (85°C) 20 A Insulation Initial Dielectric Between Open Contacts Contact Limiting Making Current 120 A Insulation Initial Dielectric Between Contacts & Coil Contact Limiting Breaking Current 20 A Contact Voltage Rating 24 VDC
Contact Limiting Continuous Current 60 A Current Rating (85°C) 20 A Insulation Initial Dielectric Between Open Contacts 500 Vrms Contact Limiting Making Current 120 A Insulation Initial Dielectric Between Contacts & Coil 500 Vrms Contact Limiting Breaking Current 20 A Contact Voltage Rating 24 VDC
Current Rating (85°C) Insulation Initial Dielectric Between Open Contacts Contact Limiting Making Current Insulation Initial Dielectric Between Contacts & Coil Contact Limiting Breaking Current 20 A Contact Voltage Rating 24 VDC
Insulation Initial Dielectric Between Open Contacts Contact Limiting Making Current Insulation Initial Dielectric Between Contacts & Coil Contact Limiting Breaking Current Contact Voltage Rating 24 VDC
Contact Limiting Making Current Insulation Initial Dielectric Between Contacts & Coil Contact Limiting Breaking Current 20 A Contact Voltage Rating 24 VDC
Insulation Initial Dielectric Between Contacts & Coil 500 Vrms Contact Limiting Breaking Current 20 A Contact Voltage Rating 24 VDC
Contact Limiting Breaking Current 20 A Contact Voltage Rating 24 VDC
Contact Voltage Rating 24 VDC
Contact Switching Load (Min) 1000mA @ 5VDC
Coil Power Rating DC 1800 mW
Coil Voltage Rating 24 VDC
Coil Resistance 324Ω
Body Features
Product Weight 35 g[1.2 oz]
Contact Features

Silver Alloy

Contact Material



Termination Features

Relay Connection Type	Plug-In
Terminal Configuration	Quick Connect Terminals
Mechanical Attachment	
Product Mounting Feature Type	Mounting Brackets
Product Mount Type	Socket
Dimensions	
Product Width	25.9 mm[1.02 in]
Product Length	25.9 mm[1.02 in]
Product Height	24.9 mm[.98 in]
Usage Conditions	
Environmental Ambient Temperature (Max)	125 °C[257 °F]
Operation/Application	
Actuating System	DC
Coil Magnetic System	Monostable
Other	
Length Class (Mechanical)	25 - 30 mm
Environmental Ambient Temperature Class	105 - 125 °C
Insulation Initial Dielectric Between Coil & Contact Class	0 - 500 V
Height Class (Mechanical)	20 - 25 mm
Width Class (Mechanical)	25 - 30 mm
Contact Current Class	30 - 50 A

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per



homogenous material. Also BFR/CFR/PVC
Free

Solder Process Capability

Not applicable for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Power Relay F






Customers Also Bought





TE Part # 1-1863005-2 UMNL 12 WAY PLUG HOUSING



TE Part # 735160 TERM, RECPT, PIDG, FAST, .250, 16-14



TE Part # 2083112-4 CABLE ASSY IND. USB-IND. USB TYPE A





TE Part # 2-917338-5 DYNAMIC 3200 VERTI. HDR ASY 4P



TE Part # K1154971 Push button switch TS-223-GE31 916



VF711H11/X839





Documents

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_3-1393303-7_S00F.3d_igs.zip

English

Customer View Model

ENG_CVM_3-1393303-7_S00F.3d_stp.zip

English

Customer View Model

ENG_CVM_3-1393303-7_S00F.2d_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use

Datasheets & Catalog Pages

Automotive Relay Application Notes

English

Product Specifications

Mini Relays, 24VDC Coil Voltage Rating, 30 - 50A Contact Current Class, Contact Arrangement 1 Form A (NO), Socket, 324 Ω Coil Resistance, Power Relay F



Definitions General Purpose Relays

English