

DIN-Signal coax f, solder/crimp, 500hm



| Part number | 09 03 000 6274 |
|--------------------|--|
| Specification | DIN-Signal coax f, solder/crimp, 500hm |
| HARTING eCatalogue | https://b2b.harting.com/09030006274 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Contacts |
|----------------------------|---|
| Series | DIN 41612 har-modular [®] |
| Type of contact | Coaxial contact |
| Description of the contact | Straight With knurled area |
| Contacts for | DIN 41612 Type M DIN 41612 Type M invers DIN 41612 Type MH 21+5 DIN 41612 Bauform M 0+2 har-modular® M module, male, angled har-modular® M module, male, straight |
| Features | lead-free |

Version

| Termination method | Solder/crimp termination |
|-----------------------|--|
| Gender | Female contact for male connectors |
| Connection type | Motherboard to daughtercard Mezzanine Extender card PCB to cable |
| Manufacturing process | Turned contacts |

Technical characteristics

| Rated current | ≤1.4 A |
|---------------|--------|
| Rated voltage | 250 V |



Technical characteristics

| Insulation resistance | >10 ⁹ Ω |
|----------------------------------|--|
| Contact resistance | ≤10 mΩ for inner contact die ≤3 mΩ for outer ferrule |
| Impedance | 50 Ω |
| Limiting temperature | -55 +125 °C |
| Return loss | >18 dB @ 1 GHz for cables RG 188 >15 dB @ 2 GHz for cables RG 188 |
| Insertion force | ≤10 N |
| Withdrawal force | ≥1 N |
| Performance level | 1 |
| Mating cycles | ≥500 |
| Test voltage U _{r.m.s.} | 0.75 kV |
| Frequency | 2 GHz |

Material properties

| Material (contacts) | Copper alloy |
|--------------------------------------|--|
| Surface (contacts) | Noble metal over Ni Mating side |
| Material (locking) | Copper alloy |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | 339476a1-86ba-49e9-ab4b-cd336420d72a |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |

Specifications and approvals

Specifications DIN 41626



Commercial data

| Packaging size | 100 |
|--------------------------------|--|
| Net weight | 2.01 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| GTIN | 5713140004191 |
| ETIM | EC000796 |
| eCl@ss | 27440204 Contact for industrial connectors |

Assembly instructions

