



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	NOTES
1	50-00007	Connector, 2.5xL20.2 mm, 4C audio plug, brass nickel plated	2	
2	30-00413	Wire, 4C TC, 26 AWG, 30V, 80C, 3.7 mm, shielded, PVC, 89A	1	
3	24-00075	Overmold, PVC, black	2	



Wiring Diagram		
50-00007	wire color	50-00007
A	Red	A
B	Black	B
C	Yellow	C
D	Green	D

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A1	5/11/2009	Added connector part number	GL <small>Digitally signed by GL Date: 2017.02.10 16:27:38 -0800</small>	RoHS compliant	
A2	8/30/2011	Updated description and connector information	Verified: PS <small>Digitally signed by PS Date: 2017.02.13 14:36:11 -0800</small>	Function test: no open, no short circuit, no intermittent	
A3	5/6/2014	Updated description	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description:	
A4	2/23/2016	Corrected barrel length dimensions		Cable, 1830 mm, 4C 2.5 mm 50-00007 plug to same, 26 AWG, 30-00413	
A5	2/10/2017	Updated notes			Size: Part number: A 053-0112R (CA-254S-MM)
					Scale: 1:2  Sheet 1 of 1