


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00024	Connector, dc plug, 5.5x2.1xL23 mm, molding style, spring contacts	1	
2	30-00395	Wire, 2C TS, 18 AWG, UL2468, 300V, 80C, 4.4 mm, VW-1, PVC, 87A	1	
3	24-00003	Overmold, PVC	1	black



Wiring Diagram	
50-00024	wire color
center	black with stripe
sleeve	black

Notes:

Functionally equivalent components may be substituted

Revision:	Date:	Description:	Prepared: GL Digitally signed by GL Date: 2018.02.01 10:21:38 -08'00'	Notes: RoHS compliant Function test: no open, no short circuit, no intermittent	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	02/01/2018	Initial release	Verified: JP Digitally signed by JP Date: 2018.02.13 14:00:24 -08'00'	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 1830 mm, 5.5x2.1x9.5 mm 50-00024 dc plug to 10 mm tinned, 18 AWG, UL2468, 30-00395 wire
					Size: A Part number: 10-02493
					Scale: 1:1 Sheet 1 of 1