


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00026	Connector, dc plug, 5.5x2.5xL23 mm, molding style, spring contacts	1	
2	50-00187	Connector, dc plug, 5.5x2.5xL20.5 mm, molding style, spring contacts	1	
3	30-00395	Wire, 2C TS, 18 AWG, UL2468, 300V, 80C, 4.4 mm, VW-1, PVC, 87A	1	
4	24-00003	Overmold, PVC	1	black
5	24-00006	Overmold, PVC	1	black



Wiring Diagram		
50-00026	wire color	50-00187
center	black with stripe	center
sleeve	black	sleeve

**Notes:**

Functionally equivalent components may be substituted

Revision:	Date:	Description:	Prepared: GL <small>Digitally signed by GL Date: 2018-02-14 09:57:24 -08'00'</small>	Notes: RoHS compliant Function test: no open, no short circuit, no intermittent	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	01/17/2018	Initial release	Verified: AW <small>Digitally signed by AW Date: 2018-02-14 11:18:42 -08'00'</small>	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 305 mm, 5.5x2.5x12 mm 50-00026 dc plug to 5.5x2.5x12 mm 90° 50-00187 dc plug, 18 AWG, UL2468
					Size: A Part number: 10-02544
					Scale: 1:1
					Sheet 1 of 1