



Screw Terminal Blocks

2000/ 3 DS

Order Info

reference number (ref. no.)	128303
PU	80
EAN	4028012106547



Type

Type	Terminal Block
connection type	screw
number of poles	3 pole
colour	naturalal
wire protection	yes

Electrical Data

rated voltage	500 V
rated current	76 A

Connection Data

cross-section rating	16.0 mm ²
cross-section rating (UL)	14-6 AWG
clamping range	0.5 - 22.0 mm ²
type of conductor	fine stranded, stranded, solid
stripping length	10.0 - 10. mm
fixing	Screw
clamping units per pole	1
contact screw assembly	1.0 x 5.5 / ∪ 2.0 Nm
mounting hole diameter	4.3 mm
socket diameter	5.40 mm
pin spacing	14.5 mm

Ambient Conditions

T _{max} ambient air (at rated current)	85 °C
T _{min} ambient air (operation)	-40 °C

Materials

insulator material	PA
contact material	brass

flammability rating acc. to UL 94	V-2
--	-----

Approvals

acc. to EN 60998	yes
-------------------------	-----

acc. to UL	yes
-------------------	-----

acc. to CSA	yes
--------------------	-----

Accessories

2000 BZ/ 3	191803
-------------------	--------

ZEL 110	196420
----------------	--------
