



## Screw Terminal Blocks

### 2000/ 3

#### Order Info

reference number (ref. no.)	128203
PU	80
EAN	4028012106486



#### Type

Type	Terminal Block
connection type	screw
number of poles	3 pole
colour	naturalal

#### Electrical Data

rated voltage	500 V
rated current	76 A

#### Connection Data

cross-section rating	16.0 mm <sup>2</sup>
cross-section rating (UL)	14-6 AWG
clamping range	0.5 - 29.0 mm <sup>2</sup>
type of conductor	fine stranded, stranded, solid
stripping length	10.0 - 10. mm
fixing	Screw
clamping units per pole	1
contact screw assembly	1.0 x 5.5 / $\cup$ 2.0 Nm
mounting hole diameter	4.3 mm
socket diameter	6.20 mm
pin spacing	14.5 mm

#### Ambient Conditions

T <sub>max</sub> ambient air (at rated current)	85 °C
T <sub>min</sub> ambient air (operation)	-40 °C

#### Materials

insulator material	PA
contact material	brass
flammability rating acc. to UL 94	V-2

## Approvals

<b>acc. to EN 60998</b>	yes
<b>acc. to UL</b>	yes
<b>acc. to CSA</b>	yes

## Accessories

<b>2000 BZ/ 3</b>	191803
<b>ZEL 110</b>	196420