# 6PCR-02-006 🗸 ACTIVE

### Buchanan | Buchanan 6 Series

TE Internal #: 6-1437651-2 Barrier Strips, Tri-Barrier, Printed Circuit Pin, Wire-to-Board, 2 Position, 9.53 mm [.375 in] Centerline, 1 Row, Buchanan 6 Series View on TE.com >



Connectors > Terminal Blocks & Strips > Barrier Strips



Barrier Strip Style: Tri-Barrier

Bottom Termination Type: Printed Circuit Pin

Connector System: Wire-to-Board

Number of Positions: 2

Centerline (Pitch): 9.53 mm [.375 in ]

## Features

## Product Type Features

Block Style	Flat Bottom
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Levels	1
Number of Positions	2
Number of Rows	1
Electrical Characteristics	
Operating Voltage	300 V
Body Features	
Primary Product Color	Black
Product Orientation	Right Angle
Barrier Strip Style	Tri-Barrier
Contact Features	

**C** For support call +1 800 522 6752

## 6PCR-02-006

Barrier Strips, Tri-Barrier, Printed Circuit Pin, Wire-to-Board, 2 Position, 9.53 mm [.375 in] Centerline, 1 Row, Buchanan 6 Series



PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	25 A
Termination Features	
Bottom Termination Type	Printed Circuit Pin
Mechanical Attachment	
Screw Head Type	Combo Phil-Slot
Screw Plating Material	Zinc Chromate
Screw Material	Steel
Top Termination Type	Wire Clamp Combo Head
Mounting Options	None
Thread Size	6-32
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Thermoplastic
Centerline (Pitch)	9.53 mm[.375 in]

## Dimensions

Wire Size.3 - 3 mm²Usage ConditionsOperating Temperature Range0 - 105 °C[0 - 221 °F]Operation/ApplicationPowerCircuit ApplicationPowerIndustry StandardsUL 94V-0UL Flammability RatingUL 94V-0Packaging Features280Packaging MethodPackageProduct ComplianceForduct ComplianceEur operation, visit the product page on TE.com>Compliant	Product Length	20.6 mm[.811 in]
Operating Temperature Range0 - 105 °C[0 - 221 °F]Operation/ApplicationPowerCircuit ApplicationPowerIndustry StandardsUL 94V-0UL Flammability RatingUL 94V-0Packaging Peatures280Packaging MethodPackageProduct CompliancePackage on TE.com>	Wire Size	.3 - 3 mm <sup>2</sup>
Operation/Application       Power         Circuit Application       Power         Industry Standards       UL Planmability Rating         UL Flammability Rating       UL 94V-0         Packaging Features       280         Packaging Method       Package         Product Compliance       Package on TE.com>	Usage Conditions	
Circuit ApplicationPowerIndustry StandardsUL 94V-0UL Flammability RatingUL 94V-0Packaging Features280Packaging MethodPackageProduct CompliancePackageFor compliance documentation, visit the product page on TE.com>	Operating Temperature Range	0 - 105 °C[0 - 221 °F]
Industry Standards         VL Flammability Rating       VL 94V-0         Packaging Features         Packaging Quantity       280         Packaging Method       Package         Product Compliance         For compliance documentation, visit the product page on TE.com>	Operation/Application	
UL Flammability Rating UL 94V-0   Packaging Features 280   Packaging Method Package   Product Compliance Package on TE.com>	Circuit Application	Power
Packaging Features         Packaging Quantity       280         Packaging Method       Package         Product Compliance       Package on TE.com>	Industry Standards	
Packaging Quantity       280         Packaging Method       Package         Product Compliance         For compliance documentation, visit the product page on TE.com>	UL Flammability Rating	UL 94V-0
Packaging Method       Package         Product Compliance       For compliance documentation, visit the product page on TE.com>	Packaging Features	
Product Compliance For compliance documentation, visit the product page on TE.com>	Packaging Quantity	280
For compliance documentation, visit the product page on TE.com>	Packaging Method	Package
For compliance documentation, visit the product page on TE.com>		
	-	
EU RoHS Directive 2011/65/EU Compliant	Tor compliance documentation, whit the product page on TE.com>	
	EU RoHS Directive 2011/65/EU	Compliant

**C** For support call +1 800 522 6752

## 6PCR-02-006

Barrier Strips, Tri-Barrier, Printed Circuit Pin, Wire-to-Board, 2 Position, 9.53 mm [.375 in] Centerline, 1 Row, Buchanan 6 Series




EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

#### Also in the Series **Buchanan 6 Series**



## **Customers Also Bought**



## 6PCR-02-006

Barrier Strips, Tri-Barrier, Printed Circuit Pin, Wire-to-Board, 2 Position, 9.53 mm [.375 in] Centerline, 1 Row, Buchanan 6 Series





## Documents

## Product Drawings 6PCR-02-006=6PCR ASSEMBLY

English

## **CAD** Files

Customer View Model

ENG\_CVM\_CVM\_6-1437651-2\_M.2d\_dxf.zip

English

## 3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_6-1437651-2\_M.3d\_igs.zip

English

Customer View Model

## ENG\_CVM\_CVM\_6-1437651-2\_M.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Datasheets & Catalog Pages 1-1773458-2\_BARRIER\_STRIPS\_QUICK\_REFERENCE\_GUIDE

English