

4-Port USB Charging Station with OTG Hub - 5V 6A / 30W USB Charger Output

MODEL NUMBER: **U280-004-OTG**



Description

Tired of searching for wall outlets or swapping out one device to charge another? Tripp Lite's U280-004-OTG Charging hub with OTG is the solution, featuring four ports for charging tablets, phones, or other mobile devices, all at the same time. It provides a single location to charge multiple devices, and its sleek, compact design keeps your charging area neat and clutter free. It features two 5V, 2A ports and two 5V, 1A ports, providing up to 6A for charging the connected devices. Furthermore, it comes with an internal power supply, eliminating the need to fumble around with bulky power adapters. When not being used for charging, it doubles as a USB OTG hub. Simply connect your OTG compatible tablet or phone to the dedicated port on the hub, and then connect up to four USB devices (flash drive, mouse, keyboard, etc.). You can now use those devices on your tablet or phone. So whether you're at home or in the office, our Charging Hub with OTG provides an ideal solution for charging your devices or expanding the functionality of your OTG compatible tablet or phone. Input: 100-240V, 50/60Hz, 1.0A / Output: 5V 6A

Features

- Features four ports for charging tablets, phones, or other mobile devices in a single location
- Includes two 5V, 2A ports and two 5V, 1A ports
- Doubles as a USB OTG Hub when not being used for charging; connect up to four USB devices (flash drive, mouse, keyboard, etc.) to your OTG compatible tablet or phone
- All four ports are USB Battery Charging (BC) specification v1.2 compliant. Supports iPad; iPhone; Samsung Galaxy (Tab, Phone, and Note); Microsoft Surface; and more
- Sleek, compact design keeps charging area neat and clutter free
- Features Over-Temperature and Over-Current detection and protection
- Internal power supply eliminates the need to fumble around with bulky power adapters
- Input: 100-240V, 50/60Hz, 1.0A / Output: 5V 6A
- P059-006 (EU) and P061-006 (UK) power cords (sold separately) available for international use

Specifications

Highlights

- Charge up to 4 tablets, phones, or other mobile devices
- Features two 5V, 2A ports and two 5V, 1A ports
- Doubles as a USB OTG Hub; connect up to four USB devices (flash drive, mouse, keyboard, etc.) to your OTG compatible tablet or phone
- All four ports are USB Battery Charging (BC) specification v1.2 compliant. Supports iPad; iPhone; Samsung Galaxy (Tab, Phone, and Note); Microsoft Surface; etc.
- Sleek, compact design keeps charging area neat and clutter free
- Input: 100-240V, 50/60Hz, 1.0A / Output: 5V 6A

Package Includes

- U280-004-OTG
- Micro-USB OTG Cable - 2.6-ft.
- C7 to NEMA 1-15P Power Cord - 3.9-ft.
- Quick Start Guide



Powering Business Worldwide

TRIPP-LITE
by **EAT•N**

OVERVIEW	
UPC Code	037332182937
Product Type	Plug in Charger
Charging Form Factor	Charging Hub
Device Compatibility	Phone; Tablet; Amazon Kindle
INPUT	
Nominal Input Voltage(s) Supported	120V AC; 230V AC
Plug Type	C7 to NEMA 1-15P
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240
Input Frequency	50/60Hz
Input Plug Type	NEMA 1-15P (NON-POLARIZED)
Input Current	120V (0.8A) / 230V (0.4A)
OUTPUT	
Overload Protection	Yes
POWER	
Power Consumption (Watts)	37.7
Power Consumption Detail	37.7W (Operating) 0.07W (Standby)
CONNECTIONS	
Number of Ports	5
Side A - Connector 1	NEMA 1-15P (NON-POLARIZED)
Side A - Connector 2	USB A (FEMALE)
Side B - Connector 1	(4) USB A (FEMALE)
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	Blue (Power)
CHARGING	
Number of Charging Ports	4
Total Charging Amps	6A
Total Charging Watts	30
Charging Method	USB
Charging Method Detail	5V - 1.5A (7W)
Charging Port Type	(4) USB A (FEMALE)
Charging Ports / Amps	(2) 1A; (2) 2A



Powering Business Worldwide



PHYSICAL	
Color	White
Material of Construction	Polycarbonate
Shipping Dimensions (hwd / in.)	2.20 x 9.50 x 6.00
Shipping Dimensions (hwd / cm)	5.59 x 24.13 x 15.24
Shipping Weight (lbs.)	0.90
Shipping Weight (kg)	0.41
Unit Dimensions (hwd / in.)	1.200 x 4.100 x 3.900
Unit Dimensions (hwd / cm)	3.05 x 10.414 x 9.91
Unit Packaging Type	Box
Unit Weight (lbs.)	0.45
Unit Weight (kg)	0.20
ENVIRONMENTAL	
Operating Temperature Range	41 to 95 F (5 to 35 C)
Storage Temperature Range	-4 to 122 F (-20 to 50 C)
Relative Humidity	20% to 80% RH, Non-Condensing
FEATURES & SPECIFICATIONS	
GaN Technology	No
Overcurrent Protection	Yes
Overvoltage Protection	Yes
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	2-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.