

Dual Wireless Charging Pad, Qi-Certified, Black

MODEL NUMBER: U280-Q02FL-BK



10W wireless charging pad transfers battery power to 2 devices at the same time without connecting cumbersome cables to them.

Features

Wireless Cell Phone Charger Delivers up to 10W for Apple and Samsung Devices

Who wants to plug and unplug power cords when you just want to charge your phones? The U280-Q02FL-BK makes charging more convenient by doing it wirelessly. Just place your Qi-certified devices on the charging pad. That's all there is to it. This wireless phone charger even works through most protective phone cases up to 5 millimeters. It charges one smartphone at 10 watts or two phones simultaneously at 5 watts each. An included power supply connects the charger to a wall outlet, surge protector or PDU.

Note: please remove any magnetic or metal objects from your phone or case before charging.

Compatible with Qi-Certified Mobile Devices to Ensure a Safe, Flawless Charge

The U280-Q02FL-BK works with all Qi smartphones, tablets and other devices from Apple, Sony, LG, Samsung, Nokia and other popular brands. It protects your expensive devices from overheating and overcharging that could lead to internal damage. Two-color LEDs monitor charging and inform you of charge status, error or over-temperature. The portable lightweight pad fits easily on your desktop or bedside table.

Highlights

- Charges 2 Apple, Google, Samsung and other Qi smartphones simultaneously at 5W each
- Intelligent 2-color LEDs indicate charging status, error or over-temperature warning
- Prevents overheating and overcharging to protect your essential devices from damage
- Charges your smartphone through its protective case to avoid the hassle of removing it
- Universally compatible with all Qi-certified smartphones and other devices

Applications

Transfer power from an AC outlet to your smartphones' batteries without the burden of carrying and connecting extra cabling

System Requirements

Compatible with all Qi-certified smartphones, tablets and other devices from popular brands including Apple, Samsung, Google, LG, Sony, Nokia, Microsoft, Motorola, ZTE and Xiaomi

Package Includes

- U280-Q02FL-BK Dual Wireless Charging Pad, Black
- External power supply with 5 ft. cord (Input: 100–240V, 50/60 Hz, 0.8A; Output: 12V 2.5A)
- (4) International plug adapters (North America, U.K., Europe, Australia)
- Quick Start Guide

Specifications

OVERVIEW	
UPC Code	037332257260
Charging Form Factor	Pad/Stand
Product Type	Wireless Charger
Device Compatibility	Phone; Tablet
Technology	Wireless

INPUT	
AC Power Adapter Plug(s)	AS/NZS 3112 Australia; BS 1363 UK; CEE 7/16 Schuko; NEMA 1-15P North America
AC Power Adapter Input Specs (V / Hz / A)	100-240V / 50/60Hz / 0.8A
AC Power Adapter Output Specs (V / A)	12V / 2.5A
AC Power Adapter Cord Length (ft.)	4.9
AC Power Adapter Cord Length (m)	1.5
Nominal Input Voltage(s) Supported	12V DC
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240
Input Plug Type	DC Plug (Barrel type)
OUTPUT	
Overload Protection	Yes
POWER	
Power Source Type	AC Adapter
DC Barrel Plug	OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve
CONNECTIONS	
Side A - Connector 1	3.5mm x 1.35mm (5V DC Barrel)
Side B - Connector 1	(2) WIRELESS CHARGING COIL
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	Blue (Power, Charging, Standby); Green (FOD, Over-Temperature Protection, Wrong Charger)
CHARGING	
Number of Charging Ports	0
Total Charging Amps	1.1
Total Charging Watts	10
Charging Method	Wireless
Charging Port Type	WIRELESS CHARGING COIL
Charging Ports Details	Charges one smartphone at 10WCharges two phones simultaneously at 5W each
PHYSICAL	
Color	Black
Material of Construction	PC + ABS
Unit Dimensions (hwd / in.)	7.677 x 0.484 x 3.543
Unit Dimensions (hwd / cm)	19.5 x 1.23 x 9.0



Powering Business Worldwide



Unit Packaging Type	Box
Unit Weight (lbs.)	0.330
Unit Weight (kg)	0.15
ENVIRONMENTAL	
Operating Temperature Range	32° to 95°F (0° to 35°C)
Storage Temperature Range	-4° to 158°F (-20° to 70°C)
Operating Humidity Range	10 to 80% RH
Storage Humidity Range	5 to 95% RH
FEATURES & SPECIFICATIONS	
GaN Technology	No
Overcurrent Protection	Yes
Overvoltage Protection	Yes
Driver Required	No
STANDARDS & COMPLIANCE	
External Power Supply Certifications	CE; UL; cUL
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	2-year limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.