



**NOTE:**

**1. MATERIAL**

- ① 1.1 Housing: PBT+GF, UL 94V-0, Black
- 1.2 Contact: C5191, Au or Tin over Nickel

**2. ELECTRIC**

- 2.1 Contact Resistance: 30 Milliohms Max.
- 2.2 Insulation Resistance: 1000 Mega ohms Min.
- 2.3 Dielectric Voltage: 500 V AC one Sec Level

3. Temperature Range: -55°C To +105°C

4. Packing: Tray

Order Code: A-BAT-CH-C1-EA-XTP2

G: Gold Flash  
Z: Tin

Ø11,10 (DRILL HOLE)  
Ø1,00 (PUNCH HOLE)

Scale	Free	TOLERANCE		Description:	
X.	±0.35	Drawn	29.11.2021	Peter	Coin Cell Holders CR1220 Type
.X	±0.25	Approved	17.10.2022	Winnie	ASSMANN WSW-NO.
.XX	±0.20				A-BAT-CH-C1-EA-XTP2
.XXX	±0.15	① Update the dimension & add the insulator color		Winnie	Drawing-No. ASS 9142 CO
DIM	TOL	② Drawn	29.11.2021	Peter	Customer-No.
Angle	TOL	modification			rev01
		Id.	Date	Name	SHEET 1 / 1

**ROHS compliant**  
unit:mm

**ASSMANN**  
components

1 2 3 4 5 6 7

A B C D E F G H