



## USB-C to DVI Active Adapter Cable (USB-C to DVI-D Dual Link M/M), 3 ft. (0.9 m)

#### MODEL NUMBER: U444-003-D





Connects your existing DVI monitor or projector to the USB-C or Thunderbolt 3 port on your tablet, laptop, notebook, smartphone or PC.

#### Features

Connects a DVI Display to Your USB-C or Thunderbolt 3 Device

- Compatible with USB-C or Thunderbolt 3 source devices that support USB DisplayPort Alternate Mode
- Ideal for giving video presentations, editing multiple documents or streaming 1080p video for digital signage
- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps

#### **Common Applications**

- Extends video from your primary display to another
- Duplicates the same video on 2 displays
- · Converts a secondary display to your primary display

#### Crystal-Clear 1080p Video

- Supports HD video resolutions up to 1920 x 1080 (1080p) @ 60 Hz
- Supports 36-bit Deep Color (12 bits per channel)
- Supports DVI digital transfer rates of 6.75 Gbps (2.25 Gbps per channel)

#### **Reversible USB-C Connector**

• Fumble-free reversible USB-C plug connects in either direction for quick connection every time

#### **Premium Construction**

- Gold-plated connectors and contacts for maximum conductivity and minimum data loss
- Foil and braid shielding protects against EMI/RFI line noise that can distort or destroy data
- Integral strain relief helps cable and connectors move freely without stress or cracking
- Durable PVC jacket designed to last a long time

#### **Highlights**

- Supports USB DisplayPort Alternate Mode for transmitting video
- Supports HD video resolutions up to 1920 x 1080 (1080p) @ 60 Hz
- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps
- Reversible USB-C plug connects in either direction
- Plug-and-play operation with no software or drivers required
- Note: This cable is unidirectional. Will only work from a USB-C port to DVI port

#### **System Requirements**

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- Display device with DVI input

#### **Package Includes**

 U444-003-D USB 3.1 Gen 1 USB-C to DVI Adapter Cable (M/M), 3 ft.



#### Ready for Instant Use

- Plug-and-play operation with no software, drivers or external power required
- 3 ft. length easy to manage in crowded environments
- Backward compatible with non-1080p displays

### **Specifications**

OVERVIEW		
UPC Code	037332202499	
Product Type	Active Cable	
Technology	DVI	
VIDEO		
Max Supported Video Resolution	1920 x 1200 (1080p)	
INPUT		
Bus Powered	Yes	
Product Length (in.)	36	
Product Length (cm.)	91.44	
Product Length (ft.)	3	
Product Length (m)	0.91	
BATTERY		
Battery Charging (5V/1.5A Port)	No	
POWER		
Power Consumption (Watts)	0.50	
CONNECTIONS		
Side A - Connector 1	USB C (MALE)	
Side B - Connector 1	DVI-D SINGLE LINK (MALE)	
Connector Plating	Gold	
PHYSICAL		
Color	Black	
Material of Construction	PVC, ABS	
Cable Jacket Color	Black	
Cable Jacket Material	PVC	





[	
Cable Jacket Rating	VW-1
Cable Length (ft.)	3
Cable Length (m)	0.91
Cable Length (in.)	36
Shipping Dimensions (hwd / in.)	9.00 x 7.00 x 0.50
Shipping Dimensions (hwd / cm)	22.86 x 17.78 x 1.27
Shipping Weight (lbs.)	0.17
Shipping Weight (kg)	0.08
Unit Dimensions (hwd / in.)	9.000 x 7.000 x 0.500
Unit Dimensions (hwd / cm)	0 x 0 x 0
Unit Packaging Type	Polybag
Unit Weight (Ibs.)	0.17
Unit Weight (kg)	0.08
ENVIRONMENTAL	
Operating Temperature Range	32° to 113°F (0° to 45°C)
Storage Temperature Range	14° to 158°F (-10° to 70°C)
BTUs	1.7 BTU/Hr
Operating Humidity Range	10% to 85% RH, Non-Condensing
Storage Humidity Range	5% to 90% RH, Non-Condensing
FEATURES & SPECIFICATIONS	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
IP68 Rated	No
IP20 Rated	No
UASP Support	No
Auto MDIX Support	No
Full Duplex Support	No
Suspend Mode Support	No
Remote Wakeup Support	No
HDCP Specification	1.3
Driver Required	No
STANDARDS & COMPLIANCE	
Product Certifications	UL Listed
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)



https://tripplite.eaton.com



# WARRANTY & SUPPORT Product Warranty Period (Worldwide) 3-year limited warranty 1000 Eaton Boulevard © 2024 Eaton. All Rights Reserved. Cleveland, OH 44122 Eaton is a registered trademark. All other trademarks United States are the property of their respective owners.

4/4