

SBS[®]X-75A

Sealed Connector



Dust - Water - Shock



Male Plug

SBS[®]X-75A

The SBS[®]X-75A sealed waterproof connectors come in multiple configurations offering up to a maximum of 140A of power and the durability of up to 5,000 mating cycles. Positive metal latches help safeguard against accidental disconnects that may be caused by vibration, while the built-in cable clamp allows for strain relief on wires.



Female Receptacle

The compact sleek high-power design of these environmentally rugged connectors makes them ideal for outdoor applications. The IP68 weatherproof rating ensures that the connector will be free of water for full protection up to 30 minutes at 6 feet in the mated conditions, or with the use of covers in unmated condition.



Panel Mount Receptacle

FEATURES

- Power & Signals or Ground
- Rated for IP68 Ingress Protection
- Positive Latching to Secure Connection for Vibration Applications
- Operating Temperatures -20°C to 105°C
- 5,000 Mating Cycles

TARGET MARKETS

- Industrial/Commercial
- Power Equipment
- Material Handling/Automation
- Agricultural/Construction
- Lawn/Garden Equipment
- Marine



Panel Mount Plug



Does your next project need Ingress Protection against harsh environments?

Contact your Anderson Power Representative today to learn more about this new connector series.

Your Best Connection™

All Data Subject to Change Without Notice SS-SBSX-75A REV 5
ECN 2023-60

©2023 Anderson Power Products, Inc. All rights reserved. A[®], Anderson Power Products[®], and SBS[®] are registered trademarks of Anderson Power Products, Inc. Anderson™ and Your Best Connection™ are trademarks of Anderson Power Products, Inc.

Anderson Power Products[®], 13 Pratts Junction Road, Sterling, MA 01564-2305
USA T: +1 978-422-3800 • www.andersonpower.com

ANDERSON POWER™