

Part Number: 06023104 Product Description: Flat Blade Appliance Dryer Motor Crimp Housing, 10 Circuit

Series Number: 42865 Status: Active

Product Category: Connector Housings Engineering Number: 42865-0001

#### **Documents & Resources**

#### **Drawings**

Drawing 006023104\_sd.pdf

**3D Models and Design Files**3D Model 006023104\_stp.zip

#### **Specifications**

Packaging Specification PK-42865-001-001.pdf Product Specification PS-43374-001-001.pdf

### **Product Environment Compliance**

### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | <b>©</b>  |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                    |
| REACH SVHC         | Not Contained per D(2023)8585-DC<br>(23 Jan 2024) |
| EU RoHS            | Compliant per EU 2015/863                         |

### **Multiple Part Product Compliance Statements**

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# **Part Details**

## General

| Status       | Active  |
|--------------|---|
| Category     | Connector Housings  |
| Series       | 42865   |
| Description  | Flat Blade Appliance Dryer Motor<br>Crimp Housing, 10 Circuit |
| Application  | Power   |
| Product Name | Flat Blade  |
| UPC          | 800753825994  |

# Agency

| CSA | LR19980 |
|-----|---------|
| UL  | E29179  |

# Physical

| Circuits (maximum)            | 10            |
|-------------------------------|---------------|
| Color - Resin                 | Natural       |
| Flammability                  | 94V-2         |
| Gender                        | Receptacle    |
| Glow-Wire Capable             | No            |
| Keying to Mating Part         | Yes           |
| Lock to Mating Part           | Yes           |
| Material - Resin              | Nylon         |
| Net Weight                    | 8.602/g       |
| Number of Rows                | 1             |
| Packaging Type                | Bag           |
| Panel Mount                   | No            |
| Pitch - Mating Interface      | 5.80mm        |
| Pitch - Termination Interface | 5.80mm        |
| Polarized to Mating Part      | Yes           |
| Stackable                     | No            |
| Temperature Range - Operating | -40° to +75°C |

## **Solder Process Data**

| Lead-Free Process Capability | N/A |
|------------------------------|-----|
|------------------------------|-----|

## Mates With / Use With

## Mates with Part(s)

| Description | Part Number |
|-------------|-------------|
| Mates With  | Dryer Motor |

## Use with Part(s)

| Description                      | Part Number  |
|----------------------------------|--------------|
| Flat Blade Female Crimp Terminal | <u>1508</u>  |
| Flat Blade Crimp Terminals       | <u>41422</u> |
| Sabre Female Crimp Terminals     | 43374        |

This document was generated on Apr 11, 2024