

# Stainless steel hinge for 2 locks door NSYPLM3025 (former version)

NSYAEDHPLM3025

#### Main

Range	Thalassa
product or component type	Hinge
Application	Multi-purpose
Nominal dimensions of the housing	- H: 300 mm W: 255 mm
mounting location	Door and enclosure
mounting support	Front plate
Range compatibility	Thalassa Thalassa PLM
Device composition	2 x hinge pin
Quantity per set	Set of 1

### Complementary

Material	Stainless steel
Operating angle	120 °

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.300 cm
Package 1 Width	0.300 cm
Package 1 Length	0.800 cm
Package 1 Weight	10.500 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	0.500 cm
Package 2 Width	3.500 cm
Package 2 Length	8.000 cm
Package 2 Weight	105.000 g
Unit Type of Package 3	S01
Number of Units in Package 3	100
Package 3 Height	15 cm
Package 3 Width	15 cm

Package 3 Length	40 cm
Package 3 Weight	1.250 kg

## **Contractual warranty**

Warranty 18 months

#### Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

#### Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information