# Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



# PLA door 1500x500 with handle

NSYDPLA155HG

### Main

Range	Thalassa
Accessory / separate part categor	Enclosure accessory
product or component type	Door
Application	Multi-purpose
For enclosure nominal dimensions	-
mounting location	Front
Range compatibility	Thalassa Thalassa PLA
Device composition	1 door locking system
Quantity per set	Set of 1

# Complementary

Material	Door: polyester reinforced with fibreglass
Colour	Door: grey (RAL 7035)
lock type	Lock 5 mm double bar
Number of locks	1
Door type	Plain
Door opening side	Reversible (120 °) Reversible (180 °)
Maximum load	30 kg/m²
Height	1500 mm
Width	500 mm

# **Packing Units**

_	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 cm
Package 1 Width	5.500 cm
Package 1 Length	154.000 cm
Package 1 Weight	11.440 kg
Unit Type of Package 2	P2M
Number of Units in Package 2	20

Package 2 Height	90.000 cm
Package 2 Width	200.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	243.800 ka

# Sustainability

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



Mercury Free



Rohs Exemption Information

Yes

### **Certifications & Standards**

REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Product Environmental Profile
No need of specific recycling operations