

Product data sheet

Specifications



PLA door 1500x750 with handle

NSYDPLA157HG

Main

Range	Thalassa
Accessory / separate part categor	Enclosure accessory
product or component type	Door
Application	Multi-purpose
For enclosure nominal dimensions	-
mounting location	Front
Range compatibility	Thalassa Thalassa PLA
Device composition	1 door locking system
Quantity per set	Set of 1

Complementary

Material	Door: polyester reinforced with fibreglass
Colour	Door: grey (RAL 7035)
lock type	Lock 5 mm double bar
Number of locks	1
Door type	Plain
Door opening side	Reversible (120 °) Reversible (180 °)
Maximum load	30 kg/m²
Height	1500 mm
Width	750 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	79.0 cm
Package 1 Width	6.0 cm
Package 1 Length	155.0 cm
Package 1 Weight	12.55 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations