

Door with locking for 2 locks PLM3025 (former version)

NSYDPLM3025G

Main

Range	Thalassa
Accessory / Separate Part Categor	Enclosure accessory
Product Or Component Type	Door
Application	Multi-purpose
For Enclosure Nominal Dimensions	-
Mounting Location	Front
Range Compatibility	Thalassa Thalassa PLM
Device Composition	1 door
Quantity Per Set	Set of 1

Complementary

Material	Door: polyester reinforced with fibreglass
Colour	Door: grey (RAL 7035)
Door Type	Plain
Door Opening Side	Right (120 °) Left
Maximum Load	50 kg/m²
Height	308 mm
Width	255 mm

Packing Units

_	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.500 cm
Package 1 Width	26.500 cm
Package 1 Length	31.500 cm
Package 1 Weight	860.000 g
Unit Type Of Package 2	S04
Number Of Units In Package 2	5
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm

Package 2 Weight	4.950 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	20
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	31.800 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Mercury Free		
Rohs Exemption Information	Yes	
Reach Regulation	REACh Declaration	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	