

Product data sheet

Specifications



internal door for PLA enclosure H1500xW500 mm

NSYPAPLA155G

Main

Range	Thalassa
Accessory / Separate Part Category	Enclosure accessory
Product Or Component Type	Door
Application	Multi-purpose
For Enclosure Nominal Dimensions	-
Mounting Location	Front side
Range Compatibility	Thalassa Thalassa PLA
Device Composition	1 door fixing elements M8 brass inserts

Complementary

Material	Aluminium
Colour	Grey (RAL 7035)
Lock Type	Lock 5 mm double bar
Number Of Locks	2
Door Type	Internal plain
Door Opening Side	Left (110 °)
Height	1398 mm
Width	398 mm
Depth	30 mm available depth between enclosure door:

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	41.0 cm
Package 1 Length	141.0 cm
Package 1 Weight	7.0 kg
Unit Type Of Package 2	P2M
Number Of Units In Package 2	10
Package 2 Height	120 cm

Package 2 Width 200 cm

Package 2 Length 40 cm

Package 2 Weight 92 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

No need of specific recycling operations