

Product data sheet

Specifications



Insulating polyester mounting plate for PLS box 54x72cm

NSYPMA5472G

Main

Range	Thalassa
Accessory / separate part categor	Mounting accessory
product or component type	Mounting plate
Device application	Multi-purpose
Enclosure nominal dimensions	- H: 540 mm W: 720 mm
mounting location	Back inserts
Mounting plate description	Insulating
Range compatibility	Thalassa Thalassa PLS
Device composition	1 mounting plate
Material	Polyester
Colour	Grey (RAL 7035)

Complementary

Fixing mode	By screws - screw type M6 - on back inserts location
Permanent permissible load	150 kg
Height	Real: 500 mm
Width	Real: 680 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.500 cm
Package 1 Width	50.000 cm
Package 1 Length	68.500 cm
Package 1 Weight	2.240 kg
Unit Type of Package 2	P12
Number of Units in Package 2	40
Package 2 Height	45.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	101.600 kg

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

No need of specific recycling operations